
# Flex PLI GTR Status

Informal Group GTR9 PH2









1-2 December 2011 Bernard Been


### Content

- ► Number of GTR legs manufactured
- ► Flex Status
- ► Leg availability



#### Number of GTR Legs Made

- ► 3 JARI prototypes
- ➤ 3 Humanetics for internal testing, demo and CAE
- ➤ 22 customer legs have been sold
- ► 12 legs are on order
- ► All customer legs have onboard DAS
- ➤ Some with optional addition channels up to 24





#### Flex Status

- ➤ All production legs have Vinyl ester bones (more durable) Some prototypes have been updated to Vinyl ester
- ➤ All legs were build passing agreed GTR static component corridors
- ► All production legs <u>pass</u> GTR <u>Pendulum</u> corridors
  - T3 and T4 are usually high and MCL is generally low
- ► Production legs consistently <u>fail</u> some <u>Inverse</u> GTR corridors
  - some tibia moment channels are too low
  - failure very repeatable
- 4 different batches of Vinyl ester bone have been used
- ► From test experience Humanetics currently manufactures bones to be as close to GTR inverse corridors as possible



## Example 2011 Production Pendulum Results

Pendulum			SN DH5646			
Date			3/21/2011	3/21/2011	4/1/2011	4/7/2011
Test site	Low	High	Plymouth	Plymouth	Nagoya	Nagoya
Peak Moment @ T1	235	272	243.29	245.57	246.97	252.70
Peak Moment @ T2	185	211	198.12	199.87	199.64	205.10
Peak Moment @ T3	135	160	152.92	154.93	151.24	156.50
Peak Moment @ T4	94	108	102.79	103.89	102.89	107.00
Peak ACL Elongation	9	11	10.02	9.99	10.03	10.20
Peak MCL Elongation	23	26	22.87	23.08	23.17	23.60
Peak LCL Elongation	2	4.5	3.24	3.18	3.19	4.30
Peak PCL Elongation	4	5.4	4.09	4.18	4.27	2.00
Femur stiffness			mid			
Femur thickness			10.44mm			
Femur Batch			B2			
Tibia stiffness			mid-high			
Tibia thickness			10.36mm			
Tibia Batch			B2			
Tibia Assembly			Pass			
Femur Assembly			Pass			
Knee Assembly			Pass			
				1 /2 *******		14/:4h
				1/2 turn to springs		With SLICE

S	SN DG0726			
4/29/2011	5/2/2011	5/16/201		
Plymouth	Plymouth	BAST		
251.00	246.83	248.30		
207.98	204.93	199.50		
159.07	155.94	150.30		
109.33	106.83	101.50		
9.23	9.07	9.90		
23.14	22.96	22.90		
3.66	3.54	3.10		
4.94	5.06	4.20		
High				
10.38mm				
B2				
High				
10.67mm				
В3				
Pass				
Pass				
Pass				

S	SN DG6304				
6/16/2011	6/16/2011	6/17/2011			
Plymouth	Plymouth	Plymouth			
244.25	244.33	243.67			
199.49	199.54	198.98			
151.61	151.77	151.08			
102.39	102.45	101.50			
9.23	9.24	9.25			
22.67	22.70	22.72			
2.86	2.86	2.86			
4.93	4.95	4.96			
MID					
?					
B2					
MID					
?					
B2					
Pass					
Pass					
Pass					

SN DH6791				
5/5/2011	5/6/2011	5/6/2011		
Plymouth	Plymouth	Plymouth		
247.76	247.71	248.41		
204.72	204.12	204.63		
156.46	155.79	153.01		
106.91	106.50	106.52		
9.55	9.90	9.68		
23.14	23.08	23.18		
4.10	3.93	3.97		
4.76	4.45	4.53		
Low				
~10.3				
В2				
Medium				
10.4				
В3				
Pass				
Pass				
Pass				



### Example 2011 Production Inverse Results

Inverse			SN DH5646	
Date			4/19/2011	4/20/2011
Test site			Plymouth	Plymouth
Pre Impact velocity	10.9	11.3	11.05	11.34
Peak Moment @ T1	237	277	0.00	257.14
Peak Moment @ T2	223	269	228.26	232.05
Peak Moment @ T3	176	204	173.37	180.00
Peak Moment @ T4	98	120	98.19	101.26
Peak ACL Elongation	8.5	10.5	8.28	8.75
Peak MCL Elongation	18	23	19.77	19.73
Peak PCL Elongation	4.5	6	0.01	5.83
Femur stiffness			mid	
Femur thickness			10.44mm	
Femur Batch			B2	
Tibia stiffness			mid-high	
Tibia thickness			10.36mm	
Tibia Batch			B2	
Tibia Assembly			Pass	
Femur Assembly			Pass	
Knee Assembly			Pass	

SN DG0726			
4/29/2011	5/16/2011		
Plymouth	BAST		
11.34	11.09		
237.73	250.30		
221.94	229.50		
169.13	177.70		
93.42	97.40		
9.27	8.70		
19.59	19.10		
5.34	5.10		
High			
10.38mm			
B2			
High			
10.67mm			
В3			
Pass			
Pass			
Pass			

SN DG6304			
6/17/2011	8/4/2011		
Plymouth	BAST		
11.24	11.15		
241.32	246.8		
222.27	224.1		
170.39	170.5		
97.06	97.3		
9.26	9.7		
19.33	20.3		
5.62	5.4		
MID			
?			
B2			
MID			
?			
B2			
Pass			
Pass			
Pass			

DH6791
4/20/2011
Plymouth
11.24
231.48
216.31
171.09
99.40
8.22
16.24
4.38
Low
~10.3
В2
Medium
10.4
В3
Pass
Pass
Dacc

DI6014
6/2/2011
Plymouth
11.24
241.01
217.43
167.68
97.11
9.55
19.42
6.27
High
?
В3
High
?
B2
Pass
Pass
Dace



## Leg Availability for Testing

- ► Humanetics proposes at least 6 legs should be tested for corridor definition at 6 labs minimum after they have been checked and certified
- ► Availability of legs for testing would depend on customer co-operation
- ► Humanetics would make their internal leg available for testing



### Thank you for your attention!

