



# Annex 3

# Part A Test Procedure and Performance Parameter

Web-Meeting Breakout Group

*Elena Paffumi*

*July 2021*

# Summary proposals/opinions

## 6.3.2. Verification procedure

(...)

The measured SOCR and measured SOCE values shall be determined by dividing the measured values for range and usable battery energy by the certified values for range and usable battery energy, respectively, **determined as described in Annex 3 to this GTR**, expressed in %. The measured SOCR and measured SOCE values shall be determined by dividing the measured values for range and usable battery energy by the certified values for range and usable battery energy, respectively, expressed in %.

$$SOCE_{measured} = \frac{UBE_{measured}}{UBE_{certified}} * 100$$

$$SOCR_{measured} = \frac{Range_{measured}}{Range_{certified}} * 100$$

# Summary proposals/opinions

		Certified and measured values proposal	pro	drawback	comment
certified	Option 1 without declaration	<ul style="list-style-type: none"> <li>➤ To define a certified UBE for PEV and OVC-HEV in the durability GTR by applying an AF based on range and/or energy consumption</li> <li>➤ To define/specify the <math>AF_{\text{range}}</math> for PEV CCT and STP</li> <li>➤ To defined a certified EAER in the durability GTR for OVC-HEV (EAER is not a declared value)</li> </ul>	No need to amend regulations	<ul style="list-style-type: none"> <li>-No declared values</li> <li>-To define parameters or give provisions in the new GTR for different regulations i.e. GTR15, UN-R-101 ...</li> </ul>	<ul style="list-style-type: none"> <li>-To check family concept</li> <li>-AF: worst for durability, or vehicle H etc.</li> </ul>
	Option 2 with declaration	<ul style="list-style-type: none"> <li>➤ Adding declaration and definition of UBE for PEVs and OVC-HEVs</li> <li>➤ Adding declaration and definition of EAER for OVC-HEV</li> </ul>	Certified values available	Amendment of regulations required	
measured	Option 1 and Option 2	<ul style="list-style-type: none"> <li>➤ To define a measured UBE for PEV and OVC-HEV in the durability GTR i.e. based on GTR15 ...</li> <li>➤ To defined a measured EAER for OVC-HEV in the durability GTR</li> </ul>			<ul style="list-style-type: none"> <li>-To be defined in the durability GTR</li> </ul>

# PEV Option 1 without declaration

The usable battery energy and pure electric range shall be calculated according to GTR#15 Amd#6 Annex 8 paragraph 4.4.2.1.1. in case of the shortened Type 1 test procedure or paragraph 4.4.2.2.1. in case of the consecutive cycle Type 1 test procedure **modifying** the following stepwise procedure

parameters	Shorten Test Procedure	Consecutive Cycle Procedure
<u>UBE<sub>measured</sub></u>	Table A8/11 Step no.1 <u>UBE<sub>measured</sub> shall be rounded according to paragraph 7. of UN-GTR#15 to the nearest whole number.</u>	Table A8/10 Step no.1 <u>UBE<sub>measured</sub> shall be rounded according to paragraph 7. of UN-GTR#15 to the nearest whole number.</u>
<u>UBE<sub>certified</sub></u>	Table A8/11 Step no.6 <u>Averaging of tests for UBE<sub>STP,avg</sub> then alignment of UBE<sub>STP,avg</sub> by applying AF<sub>PER</sub></u> <u>In the case that the interpolation method is not applied, UBE<sub>CCP,avg</sub> shall be rounded according to paragraph 7. to the nearest whole number.</u> Table A8/11 Step no.9 <u>Select the maximum UBE<sub>STP,avg</sub> and final rounding to the nearest whole number according to paragraph 7.</u>	Table A8/10 Step no.7 <u>Averaging of tests for UBE<sub>CCP,avg</sub> then alignment of UBE<sub>CCP,avg</sub> by applying AF<sub>PER</sub></u> <u>In the case that the interpolation method is not applied, UBE<sub>CCP,avg</sub> shall be rounded according to paragraph 7. to the nearest whole number.</u> Table A8/10 Step no.10 <u>Select the maximum UBE<sub>CCP,avg</sub> and final rounding to the nearest whole number according to paragraph 7.</u>

<u>Range<sub>measured</sub></u>	Table A8/11 Step no.6 or 9 <b>No rounding</b>	Table A8/10 Step no.7 or 10 <b>No rounding</b>
<u>Range<sub>certified</sub></u>	Table A8/11 Step no.6 or 9	Table A8/10 Step no.7 or 10

$$AF_{PER} = \frac{PER_{WLTP,decl}}{PER_{WLTP,avg}}$$

2.1.1.

Measured UBE values for PEVs

Parameters	Explanation
<u>UBE<sub>measured</sub></u>	UBE determined by the test procedure used for certification.

**JPN**  
under the study depend on unit or require at least three(3) significant number ?

**JPN\_49MTG**  
no rounding for measured UBE

**JPN**  
same as above

**JPN\_49MTG**  
Wh unit : whole number  
kWh unit : at least three (3) significant

**JPN**  
same as above

**JPN\_49MTG**  
Wh unit : whole number  
kWh unit : at least three (3) significant

**JPN**  
same as above

**JPN\_49MTG**  
Wh unit : whole number  
kWh unit : at least three (3) significant number

**JPN**  
nearest whole number seems to be OK

**JPN\_49MTG**

2.1.2. Certified UBE values for PEVs

Parameters	Explanation
<u>UBE<sub>certified</sub></u>	UBE certified is the adjusted usable battery energy (UBE) of the vehicle measured at the point of certification. The adjustment shall be done as follows: $UBE_{certified} = UBE_{measured@cert} * AF_{UBE,PEV}$ where: UBE <sub>measured@cert</sub> is the UBE <sub>measured</sub> at the point of certification and: $AF_{UBE,PEV} = \frac{Range_{certified}}{Range_{measured@cert}}$ where: Range <sub>certified</sub> is the manufacturer range declaration for the vehicle measured at the point of certification Range <sub>measured@Cert</sub> is the Range <sub>measured</sub> at the point of certification

In case of an interpolation family concept, the adjustment shall be done by using the values of vehicle H of the interpolation family.  
In case of test group concept, the adjustment shall be done by using the values of the test group representative.  
In case of a self-certification, the manufacturer shall provide UBE<sub>certified</sub> and give evidence how the value has been determined.

Range for PEVs

Measured Range values for PEVs

Parameters	Explanation
<u>Range<sub>measured</sub></u>	Electric range determined by the test procedure used for certification.

2.2.2. Certified Range values

Parameters	Explanation
<u>Range<sub>certified</sub></u>	Certified range is a manufacturer declaration for range at certification.

**MaN\_0904**

OPTION 1 (without UBE declaration in certification)

**MaN\_0104**

For a single vehicle, situation is clear.

For vehicles which are member of an interpolation family or member of a test group, guidance required  
→ for all these cases themselves, battery will be identical  
→ UBE certified can be applied to all vehicles in this family

**MaN\_0104**

One adjustment factor  
→ for single vehicle → clear  
→ for families or test groups: guidance below

**MaN\_0104**

This value is being provided in the certification to TAA.  
The declaration need to be identical → Must

**MaN\_0104**

This value is being provided in the certification to TAA to prove that declaration is confirmed → Must

**MaN\_0104**

Following cases need to be evaluated in Phase 2:  
- What shall be done in case of a family but no interpolation?  
- This means: no individual values would be available!  
- What is the solution for Phase 1?

**MaN\_0104**

This value is being provided in the certification to TAA.  
→ official value (will be used here)

# PEV Option 2 with declaration

## 2.1. UBE for PEVs

### 2.1.1. Measured UBE values for PEVs

Parameters	Explanation
<b>UBE<sub>measured</sub></b>	UBE determined by the test procedure used for certification.

### 2.1.2. Certified UBE values for PEVs

Parameters	Explanation
<b>UBE<sub>certified</sub></b>	Certified UBE is a manufacturer declaration for UBE at certification. In case of an interpolation family concept and in case of test group concept, there should be only one declaration for the interpolation family and the test group concept.

## 2.2. Range for PEVs

### 2.2.1. Measured Range values for PEVs

Parameters	Explanation
<b>Range<sub>measured</sub></b>	Electric range determined by the test procedure used for certification.

### 2.2.2. Certified Range values

Parameters	Explanation
<b>Range<sub>certified</sub></b>	Certified range is a manufacturer declaration for range at certification.



#### MaN\_0904

OPTION 2 (with UBE declaration in certification)



#### MaN\_0104

For a single vehicle, situation is clear.

For vehicles which are member of an interpolation family or member of a test group, guidance required  
→ for all these cases themselves, battery will be identical  
→ UBE certified can be applied to all vehicles in this family



#### MaN\_0104

The declared UBE value shall be used in the calculation of the certification test results  
→ e.g. amendment of GTR15 required



#### MaN\_0104

Following cases need to be evaluated in Phase 2:  
- What shall be done in case of a family but no interpolation?  
- This means: no individual values would be available!  
- What is the solution for Phase 1?



#### MaN\_0104

This value is being provided in the certification to TAA.  
→ official value (will be used here)

# OVC-HEV Option 1 without declaration

The usable battery energy and shall be calculated according to GTR#15 Amd#6 Annex 8 paragraph 4.3, and the equivalent all-electric range shall be calculated according to GTR#15 Amd#6 Annex 8 paragraph 4.4.4.1. **modifying** the following stepwise procedure

parameters	stepwise procedure
<u>UBE<sub>measured</sub></u>	$\Delta E_{REESS,j} = \sum_{i=1}^n \Delta E_{REESS,j,i}$ $\Delta E_{REESS,j,i} = \frac{1}{3600} \times \int_{t_0}^{t_{end}} U(t)_{REESS,j,i} \times I(t)_{j,i} dt$ <p><math>t_{end}</math> is the time at the end of the confirmation cycle j, s; then correct to charge/discharge energy balance point</p> $UBE_{corr} = UBE_{meas} + (\Delta E_{REESS,end} - \Delta E_{REESS,ave})$ <p><b>rounding to the nearest whole number according to paragraph 7. of UN GTR#15</b></p>
<u>UBE<sub>certified</sub></u>	$\Delta E_{REESS,j} = \sum_{i=1}^n \Delta E_{REESS,j,i}$ $\Delta E_{REESS,j,i} = \frac{1}{3600} \times \int_{t_0}^{t_{end}} U(t)_{REESS,j,i} \times I(t)_{j,i} dt$ <p><math>t_{end}</math> is the time at the end of the transient cycle j, s; then correct to charge/discharge energy balance point</p> $UBE_{corr} = UBE_{meas} + (\Delta E_{REESS,end} - \Delta E_{REESS,ave})$ <p><b>alignment of UBE<sub>corr</sub> by applying the ratio of measured and certified electric energy consumption</b></p> <p><b>rounding to the nearest whole number according to paragraph 7. of UN GTR#15</b></p>
<u>Range<sub>measured</sub></u>	Table A8/9 Step no.3 with modifying the following calculation formula
	$EAER = \left( \frac{M_{CO2,CS} - M_{CO2,CD,avg}}{M_{CO2,CS}} \right) \times R_{CDC}$
<u>Range<sub>certified</sub></u>	Table A8/9 Step no.8 or 9

**JPN**  
under the study depend on unit or require at least three(3) significant number?

**JPN\_49MTG**  
no rounding for measured UBE

**JPN\_49MTG**  
JPN provides the solution (EVE-46-04e) but no feedback is received so far.

**JPN\_49MTG**  
**Deleted:** how to align the measured value to declared

**JPN**  
Depend on unit Or require at least three(3) significant number

**JPN\_49MTG**  
Wh unit : whole number  
kWh unit : at least three (3) significant number

**JPN\_49MTG**  
**Deleted:** X. → notes : other UNRs (R83/R101) and regional regulations (e.g. US CFR, others) need same kind of additional specific process, if necessary  
→ ¶  
US CFR : .....¶  
→ R83 for OVC-HEV (Grid-connected hybrid electric vehicle) : .....¶  
→ R101 for PEV (BEV) : .....¶  
→ others : .....

$$AF_{EC} = \frac{EC_{WLTP,decl}}{EC_{WLTP,avg}} \quad \text{or} \quad AF_{EAER}$$

- 3.1. OVC-HEV performance parameters for Case 1
- 3.1.1. UBE for OVC-HEVs (Case 1)
- 3.1.1.1. Measured UBE values for OVC-HEVs (Case 1)

Parameters	Explanation
<u>UBE<sub>measured</sub></u>	UBE determined by the test procedure used for certification The value is calculated as follows: $UBE_{measured} = \sum_{i=1}^n \Delta E_{REESS,i}$ where: $UBE_{measured}$ is the measured electric energy change of all batteries, Wh; $\Delta E_{REESS,i}$ is the measured electric energy change of battery i, Wh; $i$ is the index number of the considered battery; $n$ is the total number of batteries; and: $\Delta E_{REESS,i} = \frac{1}{3600} \times \int_{t_0}^{t_{end}} U(t)_{REESS,i} \times I(t)_{REESS,i} dt$ where: $U(t)_{REESS,i}$ is the voltage of battery i, V; $I(t)_{REESS,i}$ is the electric current of battery i, A; $t_0$ is the time at the beginning of the charge-depleting test or full-charge test, s; $t_{end}$ is the time at the end of the confirmation cycle of the charge-depleting test or the charge-balanced cycle of the full-charge test, s.

### 3.1.1.2. Certified UBE values for OVC-HEVs (Case 1)

Parameters	Explanation
<u>UBE<sub>certified</sub></u>	UBE certified is the adjusted usable battery energy (UBE) of the vehicle measured at the point of certification. The adjustment shall be done as follows: $UBE_{certified} = UBE_{measured@cert} * AF_{UBE,OVC-HEV}$ where: $UBE_{measured@cert}$ is the UBE <sub>measured</sub> at the point of certification and: $AF_{UBE,OVC-HEV} = \frac{Range_{measured@cert}}{Range_{certified}}$ where: <u>Range<sub>certified</sub></u> is the manufacturer range declaration for the vehicle measured at the point of certification <u>Range<sub>measured@cert</sub></u> is the measured range at the point of certification  In case of an interpolation family concept, the adjustment shall be done by using the values of vehicle H of the interpolation family. In case of test group concept, the adjustment shall be done by using the values of the test group representative. In case of a self-certification, the manufacturer shall provide <u>UBE<sub>certified</sub></u> and give evidence how the value has been determined.

- 3.1.2. Range for OVC-HEVs (Case 1)
- 3.1.2.1. Measured Range values for OVC-HEVs (Case 1)

Parameters	Explanation
<u>Range<sub>measured</sub></u>	Electric range determined by the test procedure used for certification. The value is calculated as follows: $EAER_{measured} = \left( \frac{M_{CO2,CS} - M_{CO2,CD/FCT,avg}}{M_{CO2,CS}} \right) \times R_{CDC}$ where: <u>EAER<sub>measured</sub></u> is the measured equivalent all-electric range, km; <u>M<sub>CO2,CS</sub></u> is the measured CO <sub>2</sub> mass emission of the charge-sustaining (Type 1) test, g/km; <u>M<sub>CO2,CD/FCT,avg</sub></u> is the measured arithmetic average CO <sub>2</sub> mass emission of the charge-depleting (Type 1) test or full-charge-test, g/km; <u>R<sub>CDC</sub></u> is the measured length of the charge-depleting test or full-charge test, km;

### 3.1.2.2. Certified Range values for OVC-HEVs (Case 1)

Parameters	Explanation
<u>Range<sub>certified</sub></u>	Certified range is a manufacturer declaration for range at certification.

**MaN\_0104**  
Following cases need to be evaluated in Phase 2:  
- What shall be done in case of a family but no interpolation?  
- This means: no individual values would be available!  
- What is the solution for Phase 1?

**MaN\_0104**  
As EAER is no declared range value in type approval, the explanation need to be more detailed here.

**MaN\_0904**  
OPTION 1 (without UBE declaration in certification)

**MaN\_0104**  
For a single vehicle, situation is clear.

For vehicles which are member of an interpolation family or member of a test group, guidance required  
→ for all these cases themselves, battery will be identical  
→ UBE certified can be applied to all vehicles in this family

**MaN\_0104**  
One adjustment factor  
→ for single vehicle → clear  
→ for families or test groups: guidance below

**MaN\_0104**  
This value is being provided in the certification to TAA.  
→ official value (will be used here)

**MaN\_0405**  
EAER declaration required → TO DO

**MaN\_0104**  
This value is being provided in the certification to TAA to prove that declaration is confirmed → Must



# OVC-HEV Option 2 with declaration

- 3.1. OVC-HEV performance parameters for Case 1
  - 3.1.1. UBE for OVC-HEVs (Case 1)
    - 3.1.1.1. Measured UBE values for OVC-HEVs (Case 1)

Parameters	Explanation
<u>UBE<sub>measured</sub></u>	<p>UBE determined by the test procedure used for certification. The value is calculated as follows:</p> $UBE_{measured} = \sum_{i=1}^n \Delta E_{REESS,i}$ <p>where:</p> <p><math>UBE_{measured}</math> is the measured electric energy change of all batteries, Wh;</p> <p><math>\Delta E_{REESS,i}</math> is the measured electric energy change of battery i, Wh;</p> <p><math>i</math> is the index number of the considered battery;</p> <p><math>n</math> is the total number of batteries;</p> <p>and:</p> $\Delta E_{REESS,i} = \frac{1}{3600} \times \int_{t_0}^{t_{end}} U(t)_{REESS,i} \times I(t)_{REESS,i} dt$ <p>where:</p> <p><math>U(t)_{REESS,i}</math> is the voltage of battery i, V;</p> <p><math>I(t)_{REESS,i}</math> is the electric current of battery i, A;</p> <p><math>t_0</math> is the time at the beginning of the charge-depleting test or full-charge test, s;</p> <p><math>t_{end}</math> is the time at the end of the confirmation cycle of the charge-depleting test or the charge-balanced cycle of the full-charge-test, s.</p>

**MaN\_0104**

Requirement: Determination scheme for UBE need to be added to certification test procedure.

3.1.1.2. Certified UBE values for OVC-HEVs (Case 1)

Parameters	Explanation
<u>UBE<sub>certified</sub></u>	<p>Certified UBE is a manufacturer declaration for UBE at certification.</p> <p>In case of an interpolation family concept and in case of test group concept, there should be only one declaration for the interpolation family and the test group concept.</p>

**MaN\_0904**

OPTION 2 (with UBE declaration in certification)

**MaN\_0104**

For a single vehicle, situation is clear.

For vehicles which are member of an interpolation family or member of a test group, guidance required

- for all these cases themselves, battery will be identical
- UBE certified can be applied to all vehicles in this family

**MaN\_0104**

The declared UBE value shall be used in the calculation of the certification test results → e.g. amendment of GTR15 required

3.1.2. Range for OVC-HEVs (Case 1)

3.1.2.1. Measured Range values for OVC-HEVs (Case 1)

Parameters	Explanation								
<u>Range<sub>measured</sub></u>	<p>Electric range determined by the test procedure used for certification. The value is calculated as follows:</p> $EAER_{measured} = \left( \frac{M_{CO2,CS} - M_{CO2,CD/FCT.avg}}{M_{CO2,CS}} \right) \times R_{CDC}$ <p>where:</p> <table border="1"> <tr> <td><u>EAER<sub>measured</sub></u></td> <td>is the measured equivalent all-electric range, km;</td> </tr> <tr> <td><u>M<sub>CO2,CS</sub></u></td> <td>is the measured CO<sub>2</sub> mass emission of the charge-sustaining (Type 1) test, g/km;</td> </tr> <tr> <td><u>M<sub>CO2,CD/FCT.avg</sub></u></td> <td>is the measured arithmetic average CO<sub>2</sub> mass emission of the charge-depleting (Type 1) test or full-charge-test, g/km;</td> </tr> <tr> <td><u>R<sub>CDC</sub></u></td> <td>is the measured length of the charge-depleting test or full-charge test, km;</td> </tr> </table>	<u>EAER<sub>measured</sub></u>	is the measured equivalent all-electric range, km;	<u>M<sub>CO2,CS</sub></u>	is the measured CO <sub>2</sub> mass emission of the charge-sustaining (Type 1) test, g/km;	<u>M<sub>CO2,CD/FCT.avg</sub></u>	is the measured arithmetic average CO <sub>2</sub> mass emission of the charge-depleting (Type 1) test or full-charge-test, g/km;	<u>R<sub>CDC</sub></u>	is the measured length of the charge-depleting test or full-charge test, km;
<u>EAER<sub>measured</sub></u>	is the measured equivalent all-electric range, km;								
<u>M<sub>CO2,CS</sub></u>	is the measured CO <sub>2</sub> mass emission of the charge-sustaining (Type 1) test, g/km;								
<u>M<sub>CO2,CD/FCT.avg</sub></u>	is the measured arithmetic average CO <sub>2</sub> mass emission of the charge-depleting (Type 1) test or full-charge-test, g/km;								
<u>R<sub>CDC</sub></u>	is the measured length of the charge-depleting test or full-charge test, km;								

3.1.2.2. Certified Range values for OVC-HEVs (Case 1)

Parameters	Explanation
<u>Range<sub>certified</sub></u>	Certified range is a manufacturer declaration for range at certification.

**MaN\_0104**

- Following cases need to be evaluated in Phase 2:
  - What shall be done in case of a family but no interpolation?
  - This means: no individual values would be available!
  - What is the solution for Phase 1?

**MaN\_0104**

As EAER is no declared range value in type approval, the explanation need to be more detailed here.

**MaN\_0104**

This value is being provided in the certification to TAA.  
→ official value (will be used here)

# Thank you for the attention

## Q&A

Contacts Info:

EC DG JRC DIR-C Energy, Transport and Climate, Sustainable Transport Unit  
elena.paffumi@ec.europa.eu



© European Union 2021

Unless otherwise noted the reuse of this presentation is authorised under the [CC BY 4.0](https://creativecommons.org/licenses/by/4.0/) license. For any use or reproduction of elements that are not owned by the EU, permission may need to be sought directly from the respective right holders.