

R158 additional amendments

2022.3.18 (VRU-Proxi IWG #22)

JAPAN
Akinari Hirao

Requested addition

Camera case in WD

16.1.1.3. Deactivation

The system may be switched off when the vehicle detects a coupling by means of a coupling device. **In that case the monitor may be used to display other views (e.g. view of a rear-mounted camera on a trailer).**

Detection system case

17.1. System activation

The system shall be activated when the backing event starts. If proper functioning cannot be effected, either the system shall automatically shut off or the driver shall be able to deactivate the system manually.

The detection system shall remain active as long as the vehicle direction selector is in the reverse position.

In case the vehicle can detect coupling with a coupling device, the system may be switched off. **In that case the information signal may be used for informing the rear detected status. [The same characteristics of information signal may not be used for the other directions or the other kind of information.]**

Additional proposal of deletion

15.2.1.7. The options 15.2.1.1 and 15.2.1.2 only apply to the vehicle categories M1 and N1, when the distance between looking back ocular point to vehicle rear-end does not exceed 2000 mm and when the vehicle has **one seating row**.

15.2.2. The close-proximity rear-view field of vision shall be established using ambinoocular vision, the eyes being at the "driver's ocular points" as defined in paragraph 12.1. above. The fields of vision shall be determined when the vehicle is in running order as defined in the consolidated Resolution on the Construction of vehicles (R.E.3) (ECE/TRANS/WP.29/78/Rev.6, para. 2.2.5.4.), plus for M₁ and N₁ vehicles one front seat passenger (75 kg). When established through windows, the glazing shall have a total light transmission factor in accordance with UN Regulation No. 43, Annex 24.

~~In case of direct view from the driver's looking back ocular points the vertical position of rear seat headrests shall be set at the designed position of assumed to use or the highest position if the headrest has multiple position settings or at the position agreed with the Technical Service.~~

**Direct view is permitted only one seating row vehicle.
Therefore, no need to describe about rear headrest position.
This part is remaining part of past proposal.**