Comments from Japan to the document by Dr. Henry Holroyd on November 16th 2022

Committee for standardization of HFCV, Japan

(Consist of 10 experts from academia, OEMs, parts suppliers, government-affiliated organizations, etc.)

January 25th, 2023


We have deep concern on his misunderstandings, and we strongly believe that HG-SCC testing method is definitely effective to screen suitable aluminum materials for the use in high-pressure hydrogen gas container. His misunderstandings are as follows.

The actual K_{IAPP} values (K value to be applied during HG-SCC test) for the testing of fourteen Al-Mg-Si alloys (26 test pieces) including industrially produced 6061 alloy with T6 temper are ranging from 14.3 to 19.6 MPa \sqrt{m} [Itoh et al.: 2020] far below 85% (25.5 MPa \sqrt{m}) of the typical K_{IC} value (30 MPa \sqrt{m}) Dr. Holroyd quoted.

Table 3. Summary of the test results for the specimens No. 4-18 Specimen Test piece K_{IApp} (MPa√m) *∆a* (mm) 16.5 19.0 0 5 b 19.0 0 19.6 >1mm 7 b 19.6 >1mm 19.6 0.005* a 9 19.6 0 14.4 0 10 14.4 0.018 0.197* 14.3 15.9 0.017* 11 0.103* 12 18.1 0.020* 18.9 >1mm 13 b 18.7 0.839* a 18.8 0.000* 14 18.8 0.063 b 18.8 0 15 b 18.8 0 18.6 0.164 0.698 16 a 17.8 18.0 0.341* 18 18.0 0 17.9 17 18.7 0.002* 6061** 154 0

** Industrially produced material

Itoh et al.: 59th Annual Conference of Metallurgists, The Canadian Institute of Mining, Metallurgy and Petroleum, (2020), Paper 820411.



2 No data has shown that industrially produced 6061-T6 sheets fail HG-SCC test.

Results of HG-SCC test of 6061-T6 sheets

Testing lab.	Number of test pieces	Yield stress, $\sigma_{0.2}$ (MPa)	$K_{\text{IAPP}} = (=0.056\sigma_{0.2})$ (MPa $\sqrt{\text{m}}$)	Crack extension, Δa (mm)	Judgement*
A	9	322	18.0	0.00~0.06	Pass
В	2	297	16.6	0.00	Pass

* When Δa is not more than 0.16 mm, the material is judged to pass the HG-SCC test.

Request from Japan

As described above, Dr. Henry Holroyd's misunderstandings are crucial. He is urging unnecessary concerns. Hence, we strongly request to reject his document.