Level Concept Implementation in SG3

(illustration & exemplary LCA studies)

A-LCA 10th session Brussels, 2023-10-17/18

Level concept from SG3 perspective

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾	Vehicle modelling	Representativeness ²⁾	Supply chain modelling	OEM manufacturing Processes	Supplier manufactu ring process	Individual decarbo nisation measures
Level 1		Generic material compo sition & average vehicle curb weight		generic footpr	generic footprint per kg of vehicle curb weight		
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model	BOM & Material informa tion system (CMDS / IMDS ³⁾)	Global average / regional	llobal secondary data material footprints (incl. generic information for pr oduction processes)			none
	Menicle of ()HIM A			primary information for the vehicle hotspot parts	Optional: primary data for OEM's inhouse hot spot processes	INFINA MANIITARTIIRINN	
	A representative vehicle of OEM B	DS) & "part-by-part" for hotspots	SC for hotspots	secondary information for t he rest	Secondary information for the rest or average values per vehicle from OEM's Scope 1 & 2 e missions	secondary	included
	e.g. OEM A's BE V model vs. OEM B's BEV model	BOM ("part-by-part")	individual SC	regional or primary data ba sed part (& material) footpr ints	1	included	included

¹⁾ a column describing comparable objects to help you understand the concepts at each level, giving hints about how to access them by level and what data to find

²⁾ data information characteristics that can be used for evaluation

^{3) (}CDMS) Chinese Material Data System, (IMDS) International Material Data System

Granularity of possible comparison

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾
Level 1	General concept of drivetrains (e.g . BEV vs. ICEV)
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model
Level 3	A representative vehicle of OEM A VS A representative vehicle of OEM B
Level 4	e.g. OEM A's BE V model vs. OEM B's BEV model

- 1) a column describing comparable
- 2) data information characteristics tl
- 3) (CDMS) Chinese Material Data Sy

Technology-to-technology comparison Vehicle-to-vehicle comparison

Vehicle modelling granularity as main criteria

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾	Vehicle modelling
Level 1		Generic material compo sition & average vehicle curb weight
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model	BOM & Material informa tion system (CMDS / IMDS ³⁾)
Level 3	A representative vehicle of OEM A VS A representative vehicle of OEM B	DS) & "part-by-part"
Level 4	e.g. OEM A's BE V model vs. OEM B's BEV model	BOM ("part-by-part")

- 1) a column describing comparable objects to help you unde
- 2) data information characteristics that can be used for evalu
- 3) (CDMS) Chinese Material Data System, (IMDS) Internation

Generic footprint representative for technology: e.g. 3.5 kg CO2e / kg of vehicle weight x vehicle weight


List of weight sums of specific material types, aggregated over all parts

List of weight sums of specific material types, part-by-part

Increasing focus of geographic representativeness / specificity

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾	Vehicle modelling	Representativeness ²⁾
Level 1		Generic material compo sition & average vehicle curb weight	i Gional averane / I
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model	BOM & Material informa tion system (CMDS / IMDS ³⁾)	Global average / regional
Level 3	A representative vehicle of OEM A VS A representative vehicle of OEM B	BOM & Material informa tion system (CMDS / IM DS) & "part-by-part" for hotspots	Regional & individual SC for hotspots
Level 4	e.g. OEM A's BE V model vs. OEM B's BEV model	BOM ("part-by-part")	individual SC

- 1) a column describing comparable objects to help you understand the concepts at ε
- 2) data information characteristics that can be used for evaluation
- 3) (CDMS) Chinese Material Data System, (IMDS) International Material Data Syster



Modelling of supply chain / manufacturing processes as final criteria

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾	Vehicle modelling	Representativeness ²⁾	Supply chain modelling	OEM manufacturing Processes	Supplier manufactu ring process	Individual decarbo nisation measures
Level 1		Generic material compo sition & average vehicle curb weight		generic footpr	generic footprint per kg of vehicle curb weight		
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model	BOM & Material informa tion system (CMDS / IMDS ³⁾)	Global average / regional	lobal secondary data material footprints (incl. generic information for pr oduction processes)			none
	Nanicia at ()HIVI A	BOM & Material informa tion system (CMDS / IM		primary information for the vehicle hotspot parts	Optional: primary data for OEM's inhouse hot spot processes		none
Level 3	A representative vehicle of OEM B	DS) & "part-by-part" for hotspots	SC for hotspots	secondary information for t he rest	Secondary information for the rest or average values per vehicle from OEM's Scope 1 & 2 e missions	secondary	- included
Level 4	e.g. OEM A's BE V model vs. OEM B's BEV model	BOM ("part-by-part")	individual SC	regional or primary data ba sed part (& material) footpr ints	1	included	included

¹⁾ a column describing comparable objects to help you understand the concepts at each level, giving hints about how to access them by level and what data to find

²⁾ data information characteristics that can be used for evaluation

^{3) (}CDMS) Chinese Material Data System, (IMDS) International Material Data System

Exemplary studies I

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾	Vehicle modelling	Representativeness ²⁾	Supply chain modelling	OEM manufacturing Processes		Individual decarbo nisation measures
Level 1		Generic material compo sition & average vehicle curb weight		generic footpr	generic footprint per kg of vehicle curb weight		
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model	BOM & Material informa tion system (CMDS / IMDS ³⁾)	Global average / regional	plobal secondary data material footprints (incl. generic information for production processes)			none
				primary information for the vehicle hotspot parts	Optional: primary data for OEM's inhouse hot spot processes	primary information f or the manufacturing of vehicle hotspot par ts	
Level 3	A representative vehicle of OEM B	DS) & "part-by-part" for hotspots	SC for hotspots	secondary information for t he rest	Secondary information for the rest or average values per vehicle from OEM's Scope 1 & 2 e missions	secondary	- included
	e.g. OEM A's BE V model vs. OEM B's BEV model			regional or primary data ba sed part (& material) footpr ints		included	included

¹⁾ a column describing comparable objects to help you understand the concepts at each level, giving hints about how to access them by level and what data to find

Patricia Egede Environmental Assessment of Lightweight Electric Vehicles Electric Vehicles

About this book

This monograph addresses the challenge of the environmental assessment of leightweight electric vehicles. It poses the question whether the use of lightweight materials in electric vehicles can reduce the vehicles' environmental impact and compares the environmental performance of a lightweight electric vehicle (LEV) to other types of vehicles. The topical approach focuses on methods from life cycle assessment (LCA), and the book concludes with a comprehensive concept on the environmental assessment of LEVs. The target audience primarily comprises LCA practitioners from research institutes and industry, but it may also be beneficial for graduate students specializing in the field of environmental assessment.

Source:


https://link.springer.com/book/10.1007/97 8-3-319-40277-2

²⁾ data information characteristics that can be used for evaluation

^{3) (}CDMS) Chinese Material Data System, (IMDS) International Material Data System

Exemplary studies II

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾	Vehicle modelling	Representativeness ²⁾	Supply chain modelling	OEM manufacturing Processes	Supplier manufactu ring process	Individual decarbo nisation measures
Level 1		Generic material compo sition & average vehicle curb weight		generic footpr	none		
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model	BOM & Material informa tion system (CMDS / IMDS ³⁾)	Global average / regional	global secondary data mat c	none		
Level 3		BOM & Material informa tion system (CMDS / IM		primary information for the vehicle hotspot parts	Optional: primary data for OEM's inhouse ho spot processes		
Level 3	VS A representative vehicle of OEM B	DS) & "part-by-part" for hotspots	SC for hotspots	secondary information for t he rest	Secondary i for the rest values per v OEM's Sco missi	Ricardo Ener	gy & Envir
Level 4	e.g. OEM A's BE V model vs. OEM B's BEV model		individual SC	regional or primary data ba sed part (& material) footpr ints	inclu	esults fro	om the



Determining the environmental impacts of conventional and alternatively fuelled vehicles through LCA | viii

Determining the environmental impacts of

conventional and alternatively

fuelled vehicles through LCA

- 1) a column describing comparable objects to help you understand the concepts at each level, giving hints about how to acc
- 2) data information characteristics that can be used for evaluation
- 3) (CDMS) Chinese Material Data System, (IMDS) International Material Data System

Results from the application of the methodology

The implementation of the developed methodology has provided results for the study covering:

- Two high-level scenarios based on analysis supporting the Commission's Long-Term Strategy (Commission Communication COM(2018) 773), i.e. Baseline and a lower carbon future - Tech1.5 scenario, consistent with the EU contribution to meeting the Paris Agreement objective of keeping global temperature increase to a 1.5 °C max).
- 14 different electricity production chains, covering the EU28 and its individual Member States (relevant for vehicle manufacturing, and electric vehicle operation), and five other world regions (China, S. Korea, Japan, the US and the global average) (for manufacturing only).
- 60 different liquid and gaseous fuel production chains, covering 5 fuel categories, 21 feedstocks, and over 20 processes, plus two fuel mix/blend scenarios for each fuel category.
- 65 different generic vehicle type/powertrain combinations, across six light- and heavy-duty vehicle body types.
- 14 different sensitivities exploring the significance and impacts of key assumptions and uncertainties for the comparative analysis of different vehicles/powertrain and fuel types.

Source:

https://op.europa.eu/en/publication-detail/-/publicatio n/1f494180-bc0e-11ea-811c-01aa75ed71a1

Exemplary studies III

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾	Vehicle modelling	Representativeness ²⁾	Supply chain modelling	OEM manufacturing Processes	Supplier manufactu ring process	Individual decarbo nisation measures	
Level 1		Generic material compo sition & average vehicle curb weight		generic footpr	b weight	none		
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model	BOM & Material informa tion system (CMDS / IMDS ³⁾)	Global average / regional	global secondary data mat c	none			
Level 3	A representative vehicle of OEM A VS	BOM & Material informa tion system (CMDS / IM		primary information for the vehicle hotspot parts	Optional: primary data for OEM's inhouse hot spot processes			
	A representative vehicle of OEM B		SC for hotspots	secondary information for t he rest	Secondary information for the rest or average values per vehicle from OEM's Scope 1 & 2 e missions	secondary information for the		nodeling In by Energie nouvelle
	e.g. OEM A's BE V model vs. OEM B's BEV model	BOM ("part-by-part")		regional or primary data ba sed part (& material) footpr ints		included	included	anufactu 00 ·····



A function of electrification level, end-user behavior, fuel, industrial and energy sector key parameters

179

E10

RI: 1 day

As powertrains diversify in their electrification levels – Hybrids (HEV), Plug-in Hybrids (PHEV) and

Battery Electric Vehicles (BEV) - along with the fuel production pathways - fossil and renewable

routes - the carbon footprint over their life cycle heavily depends on their use cases (e.g. driving profile) and context of use (e.g. carbon intensity of electricity). This interactive tool allows to design

several scenarios combining these parameters and to compare their environmental performance.

15kWh

231

E10

RI: None

2kWh

\$ 200

Microsoft Power BI

162

(Leer)

RI: None

60kWh

Life cycle assessment (LCA) of greenhouse gas Please click on the emissions from passenger cars in real-world conditions nformation buttons t nufacture ●Electricity ●Fuel WTT ●Fuel TTW minus Recycled CO2 ●Recycled CO2 ······ Total LCA GHG

213

RI: 3 days

2 4 6 8 10 2 4 6 8 10 15 20 30 Total lifetime mileage [km]

Battery capacity [kWh]

Vehicles

To reset to default parameters, please use the page refresh button of your browser

Recharge interval (RI) for PHEVs [days] 0.5 1.0 2.0 3.0 4.0 5.0 6.0 7.0 8.0 9.0 10.0

Electricity carbon intensity gCO2eq/kWh Mostly fossil, available today E10 - fossil gasoline blended with 10% renewable ethanol 100% renewable Diesel, available today HVO, made from renewable vegetable oil and waste cooking oil

100% renewable, future fuel e-Diesel, made from renewable electricity and captured CO2

e-gasoline, made from renewable electricity and captured CO2

+ 99 % f 💆 in 😢

- 1) a column describing comparable objects to help you understand the concepts at each level, giving hints about how to access them by level and what data to find
- 2) data information characteristics that can be used for evaluation
- 3) (CDMS) Chinese Material Data System, (IMDS) International Material Data System

https://www.carsco2comparator.eu/ for cars https://hdvco2comparator.eu/ for trucks


Exemplary studies IV

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾	Vehicle modelling	Representativeness ²⁾	Supply chain modelling	OEM manufacturing Processes	Supplier manufactu ring process	Individual decarbo nisation measures
Level 1		Generic material compo sition & average vehicle curb weight		generic footpr	generic footprint per kg of vehicle curb weight		
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model	BOM & Material informa tion system (CMDS / IMDS ³⁾)	Global average / regional	lobal secondary data material footprints (incl. generic information for p oduction processes)			none
Level 3		BOM & Material informa tion system (CMDS / IM		primary information for the vehicle hotspot parts	Optional: primary data for OEM's inhouse hot spot processes	primary information f or the manufacturing of vehicle hotspot par ts	
	A representative vehicle of OEM B	DS) & "part-by-part" for hotspots	SC for hotspots	secondary information for t	Secondary information for the rest or average values per vehicle from OEM's Scope 1 & 2 e missions	secondary	moluded
Level 4	e.g. OEM A's BE V model vs. OEM B's BEV model	BOM ("part-by-part")		regional or primary data ba sed part (& material) footpr ints		included	included

¹⁾ a column describing comparable objects to help you understand the concepts at each level, giving hints about how to access them by level and what data to find

Source:

https://group.mercedes-benz.com/sustainability/environmental-check/eqe.html



²⁾ data information characteristics that can be used for evaluation

^{3) (}CDMS) Chinese Material Data System, (IMDS) International Material Data System

Exemplary studies V

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾	Vehicle modelling	Representativeness ²⁾	Supply chain modelling	OEM manufacturing Processes	Supplier manufactu ring process	Individual decarbo nisation measures
Level 1		Generic material compo sition & average vehicle curb weight		generic footpr	generic footprint per kg of vehicle curb weight		
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model	BOM & Material informa tion system (CMDS / IMDS ³)	Global average / regional	lobal secondary data material footprints (incl. generic information for production processes)			none
Lovel 2				primary information for the vehicle hotspot parts	Optional: primary data for OEM's inhouse hot spot processes		none
	A representative vehicle of OEM B	DS) & "part-by-part" for hotspots	SC for hotspots	secondary information for t he rest	Secondary information for the rest or average values per vehicle from OEM's Scope 1 & 2 e missions	secondary	moluded
Level 4	e.g. OEM A's BE V model vs. OEM B's BEV model	BOM ("part-by-part")		regional or primary data ba sed part (& material) footpr ints		included	included

¹⁾ a column describing comparable objects to help you understand the concepts at each level, giving hints about how to access them by level and what data to find

Source: Renault Group, on demand

Renault Group

LIFECYCLE ASSESSMENT



CAPTUR E-Tech plug-in hybrid CAPTUR 1.3 TCE EDC (1st & 2nd gen.)

²⁾ data information characteristics that can be used for evaluation

^{3) (}CDMS) Chinese Material Data System, (IMDS) International Material Data System

Exemplary studies VI

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾	Vehicle modelling	Representativeness ²⁾	Supply chain modelling	OEM manufacturing Processes	Supplier manufactu ring process	Individual decarbo nisation measures
Level 1		Generic material compo sition & average vehicle curb weight		generic footpr	generic footprint per kg of vehicle curb weight		
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model	BOM & Material informa tion system (CMDS / IMDS ³⁾)	Global average / regional	lobal secondary data material footprints (incl. generic information for p oduction processes)			none
Level 3		BOM & Material informa tion system (CMDS / IM	Regional & individual			primary information f or the manufacturing of vehicle hotspot par ts	none
	A representative vehicle of OEM B	DS) & "part-by-part" for hotspots	SC for hotspots	secondary information for t	Secondary information for the rest or average values per vehicle from OEM's Scope 1 & 2 e missions	secondary	metuded
Level 4	e.g. OEM A's BE V model vs. OEM B's BEV model	BOM ("part-by-part")	individual SC	regional or primary data ba sed part (& material) footpr ints		included	included

¹⁾ a column describing comparable objects to help you understand the concepts at each level, giving hints about how to access them by level and what data to find

Source:

https://www.volvocars.com/images/v/-/media/Market-Assets/INTL/Applications/DotCom/PDF/C40/Volvo-C40-Recharge-LCA-report.pdf



²⁾ data information characteristics that can be used for evaluation

^{3) (}CDMS) Chinese Material Data System, (IMDS) International Material Data System


Exemplary studies VII

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾	Vehicle modelling	Representativeness ²⁾	Supply chain modelling	OEM manufacturing Processes	Supplier manufactu ring process	Individual decarbo nisation measures
Level 1		Generic material compo sition & average vehicle curb weight		generic footpr	generic footprint per kg of vehicle curb weight		
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model	BOM & Material informa tion system (CMDS / IMDS ³)	Global average / regional	lobal secondary data material footprints (incl. generic information for p oduction processes)			none
Level 3				primary information for the vehicle hotspot parts			
A	A representative vehicle of OEM B	DS) & "part-by-part" for hotspots	SC for hotspots	secondary information for t	Secondary information for the rest or average values per vehicle from OEM's Scope 1 & 2 e missions	secondary	mciadea
Level 4	e.g. OEM A's BE V model vs. OEM B's BEV model	BOM ("part-by-part")		regional or primary data ba sed part (& material) footpr ints		included	included

¹⁾ a column describing comparable objects to help you understand the concepts at each level, giving hints about how to access them by level and what data to find

OEM internal comparison of two specific vehicle models

Source: Volkswagen Group



²⁾ data information characteristics that can be used for evaluation

^{3) (}CDMS) Chinese Material Data System, (IMDS) International Material Data System

Exemplary studies | overview

SUPPLY CHAIN & PRODUCTION	Possible Comparison ¹⁾	Vehicle modelling	boson below to light the second of the secon
Level 1		Generic material compo sition & average vehicle curb weight	Assessment of Conventional and alternatively fuelled vehicles through LCA
Level 2	General concept of drivetrains (e.g. BEV vs. ICEV) based on exemplary "real" car vehicle model	BOM & Material informa tion system (CMDS / IMDS ³⁾)	Renault Group LIFECYCLE ASSESSMENT Softe 2 to a special page. Nomination.
	A representative vehicle of OEM A VS A representative vehicle of OEM B		METHODOLOCY TECHNICAL C
	e.g. OEM A's BE V model vs. OEM B's BEV model		Level

