| ITEMS | | Monitored |
|---|-----------------------|----------------------------|
| Components | Failure type | by self-test function ? |
| AECD Control Unit | Internal failure | yes |
| External Mobile network communication device | Electrical connection | yes |
| External GNSS receiver | Electrical connection | yes |
| External Mobile network communication antenna | Electrical connection | yes |
| External GNSS antenna | Electrical connection | yes |
| Crash Control Unit | Electrical connection | yes |
| Power supply | Electrical connection | yes |
| Loudspeaker | Electrical connection | yes/no |
| Microphone | Electrical connection | yes/no |
| Manual call button | Electrical connection | yes/no |
| Status indicator | Electrical connection | yes/no |
| SIM | not present | yes/no |
| No communication failures | ??? | yes/no |
| State of Health of dedicated battery | ??? | yes/no |

If the above listed components are combined and not detachable, they should I

| If no : technical reasons prohibitive of monitoring |
|---|
| Not Appplicable |
| |
| |
| |
| |
| |
| |
| |
| |

be considered as one component.

| Comments | | |
|--|--|--|
| Internal failure = e.g. hardware failure, watch-dog, software checksum, software image integrity, | | |
| | | |
| | | |
| e.g. crash detection sensor system, triggering device, | | |
| (in table 1 : dedicated battery is connected) | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |