

Based on consolidated doc. after the DE proposal (ACSF-06-05)

- Current Text of the Regulation No. 79 (Rev. 2) is marked in black characters.
- Comments of ACSF-05-16 (Homework, Remarks etc.) are removed for better readability
- Agreed new text is marked in **bold black** and ~~black strikethrough~~ characters.
- New text which was not confirmed during the 5th session is kept in **bold red** characters
- New proposals by Germany are marked in **bold green** and ~~green strikethrough~~ characters.
- Proposals from EC are underlined.

Formatiert: Schriftfarbe: Blau

### Proposal for amendments to Regulation No. 79 to include ACSF > 10 km/h

2.3.4. "Advanced Driver Assistance Steering System" means a system, additional to the main steering system, that provides assistance to the driver in steering the vehicle but in which the driver remains at all times in primary control of the vehicle. It may only include one or several of the following functions:

Formatiert: Schriftfarbe: Blau, Englisch (Großbritannien)

Amend paragraph 2.3.4.1. to read:

2.3.4.1. "Automatically commanded steering function" (ACSF) means the function ~~within a complex electronic control system~~ where actuation of the steering system can result from automatic evaluation of signals initiated on-board the vehicle, possibly in conjunction with passive infrastructure features, to generate continuous control action ~~in order to assist the driver.~~

Formatiert: Schriftfarbe: Blau, Englisch (Großbritannien), Durchgestrichen

Formatiert: Schriftfarbe: Blau, Englisch (Großbritannien)

Formatiert: Schriftfarbe: Blau

Formatiert: Schriftfarbe: Blau, Englisch (Großbritannien)

Formatiert: Schriftfarbe: Blau

Formatiert: Schriftfarbe: Blau, Englisch (Großbritannien)

Formatiert: Schriftfarbe: Blau

Formatiert: Englisch (Großbritannien)

2.3.4.1.1. **Category A ACSF means, a function that operates at a speed no greater than 10 km/h to assist the driver, on demand, in low speed manoeuvring or parking operations.**

2.3.4.1.2. **ACSF Category B1 means a function which is (initiated/)activated by the driver and which continuously assists the driver in keeping the vehicle within the chosen lane, and needing an input from the driver on the steering system at least every [30] seconds (by influencing the lateral movement of the vehicle).**

Kommentiert [AL21]: Switch on/off

2.3.4.1.3. [**"ACSF Category B2 means a function which is (initiated/)activated by the driver and which keeps the vehicle within its lane for extended periods without further driver command/confirmation lane by influencing the lateral movement of the vehicle.**]

Kommentiert [AL22]: We have to be more consistent in the terms used.

Kommentiert [AL23]: (without needing an input from the driver on the steering system every 30 seconds)

[2.3.4.1.4. **Category C ACSF means, ~~a Category B1 or B2 System including~~ a function which can perform a single manoeuver (e.g. lane change) when commanded by the driver.**

Kommentiert [AL24]: Initiated?

- 2.3.4.1.5. Category D ACSF means, ~~a Category B2-System including~~ a function which can indicate the possibility of a single manoeuvre (e.g. lane change) but performs that function only following a confirmation by the driver.]
- 2.3.4.1.6. Category E ACSF means, a Category B2-System including a function which is [initiated/activated] by the driver and which can continuously determine the possibility of a manoeuvre (e.g. lane change) and complete these manoeuvres for extended periods without further driver command/confirmation.

*Amend paragraph 2.3.4.2. to read:*

- 2.3.4.2. "Corrective steering function" means the discontinuous control function ~~within a complex electronic control system~~ whereby, for a limited duration, changes to the steering angle of one or more wheels may result from the automatic evaluation of signals initiated on-board the vehicle, in order to maintain the basic desired path of the vehicle or to influence the vehicle's dynamic behaviour. A function which allows the vehicle to stay in its lane with no input from the driver on the steering system for more than [15] seconds shall be considered as an ACSF category B system and not a corrective system.

Formatiert: Schriftfarbe: Blau

Systems that do not themselves positively actuate the steering system but that, possibly in conjunction with passive infrastructure features, simply warn the driver of a deviation from the ideal path of the vehicle, or of an unseen hazard, by means of a tactile warning transmitted through the steering control, are also considered to be corrective steering.

*Insert new paragraph 2.4.8. to read*

- 2.4.8. For Automatically commanded steering functions
  - 2.4.8.1. "Lane" means one of the longitudinal strips into which a roadway is divided.
  - 2.4.8.2. "Visible Lane markings" means delineators intentionally placed on the borderline of the lane that are directly visible by the driver while driving (e.g. not covered by snow, etc.).
  - 2.4.8.3. "Lead vehicle" means a vehicle driving in front of the vehicle equipped with ACSF.
  - 2.4.8.4. "Lane change manoeuvre" means a manoeuvre in which the vehicle changes from its initial lane to an adjacent lane
  - 2.4.8.5. "Specified maximum speed  $V_{smax}$ " means the maximum speed up to which an ACSF is designed to operate **under normal operating conditions.**
  - 2.4.8.6. "Specified minimum speed  $V_{smin}$ " means the minimum speed ~~up~~ **down** to which an ACSF is designed to operate **under normal operating conditions.**

- 2.4.8.7. **"Specified maximum lateral acceleration  $a_{v_{smax}}$ "** means the maximum lateral acceleration up to which an ACSF is designed to operate **under normal operating conditions**.
- 2.4.8.8. **"Normal operating conditions"** mean that the ACSF system is active and does **not either carry out a transition procedure nor a Minimal Risk Manoeuvre nor an Emergency Manoeuvre [or fail safe manoeuvre]**.
- 2.4.8.9. **"Transition demand"** means an instruction from the ACSF **that the driver has to take over control of the steering task again**.
- 2.4.8.10. **"Transition procedure"** means the sequence of providing a transition demand by the system, taking over steering control by the driver and deactivation of the ACSF.
- 2.4.8.11. **"Conditions for operation"** mean circumstances like traffic situation, road category, quality of lane markings, vehicle speed, curvature of the road, lighting, sensor capabilities etc. specified by the vehicle manufacturer, where the system is designed to operate.
- 2.4.8.12. **"System boundaries"** mean all circumstances from which on the conditions for operation are not fulfilled anymore.
- 2.4.8.13. **"ACSF status"** means any distinct operational mode of the ACSF like "switched off" "switched on", "available to be activated", "activated" etc.
- 2.4.8.14. **"Driver availability recognition [system/function]"** means a function able to assess driver's physical availability to respond to a transition demand from an ACSF system.
- 2.4.8.15. **"Minimal risk manoeuvre"** means a procedure aimed at minimizing risks in traffic, which is automatically performed by the system, e.g. when the driver does not respond to a transition demand
- 2.4.8.16. **"Emergency Manoeuvre"** is a manoeuvre performed by the system in case of a sudden unexpected event in which the vehicle is in imminent danger to **collide with another object**, with the purpose to avoid or mitigate a collision.
- 2.4.8.17. **"Protective braking"** means an application of the brakes of the vehicle by the system in order to decelerate the vehicle with the purpose of avoiding or mitigating a collision.
- [2.4.8.18. " Data Storage System for ACSF (DSSA)" means a data recording medium to record ACSF system operation data including data of Driver availability Recognition System.]**

Amend paragraph 5.1.6.1. to read:

- 5.1.6.1. Whenever an Automatically Commanded Steering function becomes operational, this shall be indicated to the driver. ~~and the control action shall be automatically disabled if the vehicle speed exceeds the set limit of 10 km/h by more than 20 per cent or the signals to be evaluated are no longer being received.~~ Any termination of control shall produce a ~~short but distinctive driver warning by a visual signal and either an acoustic signal or by imposing a tactile warning signal on the steering control.~~ **[especially, in case of category E termination of control is described]** in accordance with the requirements of paragraph 5.4.3.

Kommentiert [AL25]: OICA: mae example and turn the sentence positively. UK to reword the para.

Kommentiert [AL26]: Do we need this. Seems similar to transition demand.

Kommentiert [AL27]: Only?

*Insert new paragraph 5.4.3. Renumber paragraph 5.4.3. as 5.4.4.*

#### **5.4.3. Special Warning Provisions for Automatically Commanded Steering Functions**

**5.4.3.1. Any termination of operation control initiated by the system other than specified in 5.6.1.4.7 shall produce a distinctive driver warning including visual warning and either an acoustic warning or an haptic warning until the driver has resumed steering control.**

*Amend paragraph 5.5.2. to read:*

5.5.2. It shall be possible to verify in a simple way the correct operational status of those Complex Electronic Systems, which have control over steering. If special information is needed, this shall be made freely available. **It shall be possible to verify the correct operational status of those Electronic Systems by a visible observation of the failure warning signal status, following a "power-ON" and any bulb check.**

**In the case of the failure warning signal being in a common space, the common space must be observed to be functional prior to the failure warning signal status check.**

**[In the case of an ACSF system able to operate at higher speed than 10km/h, it shall be possible to confirm the failure warning signal status via the use of an electronic communication interface.]**

**In the case of an ACSF system it shall be possible to confirm the valid software version of the system via the use of an electronic communication interface.**

**Kommentiert [OK8]:** for this purpose, information from the manufacturer is needed, namely which software version is the valid one. This is now additionally stated in § 5.6.1.3 "system information data"

*Amend paragraph 5.5.2.1. to read:*

5.5.2.1. At the time of Type Approval the means implemented to protect against simple unauthorized modification to the operation of the verification means chosen by the manufacturer (e.g. warning signal) shall be confidentially outlined.

Alternatively this protection requirement is fulfilled when a secondary means of checking the correct operational status is available, **e.g. by using an electronic communication interface.**

*Insert new paragraph 5.6*

#### **5.6 Special Provisions for Automatically Commanded Steering Functions**

**Information about the transition procedure and the consequences of delayed or omitted take over of the steering shall be provided to the users of the vehicle.**

##### **5.6.1. Special Provisions for Category E ACSF**

**Any system of Category E ACSF shall fulfill the following requirements.**

##### **5.6.1.1. General**

- 5.6.1.1.1. The system shall be active (deliver automatic steering) only after a deliberate action of the driver and if the conditions for operation of the system are fulfilled (all associated functions – e.g. brakes, accelerator, steering, camera/radar/lidar etc. are working properly).
- 5.6.1.1.2. The vehicle shall be equipped with a means for the driver to activate and deactivate the system. The deactivation shall be possible at any time. The activation of the system shall not be possible if the driver is not in the driver seat or if he does not wear its seatbelt.
- 5.6.1.1.3. ~~If the driver is steering the driver is overriding the ACSF by steering manually, ACSF shall be deactivated automatically.~~ Steering by the driver shall override steering by the system. Braking or accelerating by the driver shall override speed selection by the system or initiate a transition demand.
- 5.6.1.1.4. The specified maximum speed  $v_{\text{smax}}$  shall not have a value of more than 130 km/h
- ~~5.6.1.1.4. The system shall not induce in normal driving situations a lateral acceleration of more than  $3 \text{ m/s}^2$ .~~
- 5.6.1.1.5. The specified maximum lateral acceleration  $a_{y\text{smax}}$  shall not have a value of more than  $3 \text{ m/s}^2$  and of less than  $1 \text{ m/s}^2$ .
- 5.6.1.1.6. The activated system shall at any time control the movement of the vehicle in such a way that the vehicle does not induce any safety critical situations and that the movements of the vehicle are clear to other road users.
- 5.6.1.1.7. The system status shall be indicated to the driver by a visual signal.
- The indication shall [at least] distinguish between the system status **manual stand-by Mode**, active Mode and failure **Mmode**.
- The indication shall be present as long as the relevant system status persists.
- When the system is **manually** switched off by the driver, the indication of **manual stand-by Mmode** and failure **Mmode** may be suppressed.
- Any change in system status shall be indicated by a visual and either an acoustic or haptic signal.**
- 5.6.1.1.8. The vehicle shall be equipped with means to **monitor at any times when ACSF is active a minimum range to the front ( $s_{\text{Front}}$ ), to the right ( $s_{\text{side}}$ ), and to the left side ( $s_{\text{side}}$ ) and behind ( $s_{\text{Rear}}$ ) the vehicle with the purpose to avoid or to mitigate collisions.**
- 5.6.1.1.8.1. **The minimal range in front ( $s_{\text{Front}}$ ) of the ACSF vehicle shall be calculated according to the following formula:**
- $$s_{\text{Front}} = v_{\text{ACSF}}^2 / (2 \cdot a_{\text{ACSF}})$$
- where:**

Kommentiert [OK9]: this § was redundant with § 5.6.1.1.5.

$S_{Front}$  = relative distance between the vehicle ~~under test (VUT)~~ equipped with ACSF and the vehicle driving in front, measured in meters from the front edge of the ~~VUT~~ vehicle equipped with ACSF to the rear end of the vehicle driving in front.

$v_{ACSF}$  = speed of the vehicle equipped with ACSF ~~under test~~ measured in m/s

$a_{ACSF}$  = 3,7 m/s<sup>2</sup> = feasible deceleration under wet conditions

Justification  $a_{VUT}$ : ACSF 04-05

5.6.1.1.8.2. The minimal range to the rear ( $S_{Rear}$ ) of the ACSF vehicle shall be calculated according to the following formula:

$$S_{Rear} = d_{reaction, rear} + d_{brake, rear} + d_{safety, rear}$$

with:

$$d_{reaction, rear} = (v_{rear} - v_{VUT}) * t_{reaction}$$

$$d_{brake, rear} = \frac{(v_{rear} - v_{ACSF})^2}{2 * a_{brake}}$$

$$d_{safety, rear} = v_{ACSF} * t_d$$

where:

$S_{Rear}$  = relative distance between the vehicle ~~under test (VUT)~~ equipped with ACSF and the vehicle behind, measured in meters from the rear edge of the ~~VUT~~ vehicle equipped with ACSF to the front end of the vehicle behind.

$d_{reaction, rear}$  = relative distance of the vehicle driving behind the ~~VUT~~ vehicle equipped with ACSF caused by the reaction of the driver to brake, measured in meters

$t_{reaction}$  = 1,2 s = reaction time of the driver driving the vehicle behind the ~~VUT~~ vehicle equipped with ACSF needed to execute the braking and to built up the full braking force, measured in seconds

$d_{brake, rear}$  = braking distance of the vehicle driving behind the ~~VUT~~ vehicle equipped with ACSF, measured in meters

$d_{safety, rear}$  = safety distance between the ~~vehicle under test (VUT)~~ vehicle equipped with ACSF and the vehicle driving behind, measured in meters

$t_d$  = 1,0 s = safety time gap to ~~VUT~~ vehicle equipped with ACSF after braking, measured in seconds

$v_{rear}$  = [36,1 m/s] speed of the vehicle driving behind the ~~vehicle under test (VUT)~~ vehicle equipped with ACSF, measured in m/s.

$v_{VUT}$  = speed of the ~~vehicle under test (VUT)~~ vehicle equipped with ACSF, measured in m/s.

$a_{brake}$  = 3 m/s<sup>2</sup> = admissible deceleration of the vehicle driving behind the ~~vehicle under test (VUT)~~ vehicle equipped with ACSF

5.6.1.1.8.3. The minimal range to the left and to the right (side) shall be at least 7 m (measured from the medium longitudinal centerline of the vehicle *equipped with ACSF*)

5.6.1.1.9. The vehicle shall fulfill the tests for Category E as specified in Annex 7.

5.6.1.2. Normal Operation of ACSF category E

#### LANE KEEPING

5.6.1.2.44. As long as a lane change manoeuvre is not initiated, the activated system shall at any time prior and after a lane change manoeuvre ensure that the vehicle is kept on its lane and does not cross any lane marking. (Alternative : the system shall be equipped with a category B2 system which ensures that the vehicle is kept on its lane and does not cross any lane marking ), when tested in the conditions defined in Annex 7, paragraph 3.1.1 (FU1 test) a safe lateral distance to other road users. The vehicle manufacturer shall provide documentation about how such a safe distance is achieved to the technical service.

#### Lane change

5.6.1.2.1. Any lane change manoeuvre ~~shall~~ may be initiated only if:

~~-(a) the vehicle is travelling on a road section upon which is not dedicated to pedestrians or bicyclists are not permitted and which has a [physical or constructional] separation of traffic moving in opposite directions and which has at least two lanes for the direction the vehicle is driving and~~

~~-any traffic that can affect the safe manoeuvre shall be identified by equipment installed on the vehicle and~~

~~-(c) the vehicle equipment can analyze speed and distance of the identified traffic is sufficient to ensure a safe manoeuvre (e.g. does not cause a deviation to the flow, or direction of other traffic or considering left- or right-hand traffic), and~~

5.6.1.2.2. ~~— (d) after if a lane change manoeuvre is carried out, the correspondent direction indicator lamps shall be has been automatically activated minimum for at least 3 s .~~

~~a) prior to the steering operation start of the lane change manoeuvre or~~

~~b) prior the vehicle has touched the lane markings~~

5.6.1.2.3. The lane change manoeuvre shall be ~~completed, except~~ aborted in the case of the system detects an imminent critical situation or if the driver the system is

Formatiert: Einzug: Erste Zeile: 0 cm

Kommentiert [AL210]: definition?

~~overridden-overrides the system~~ by the steering of the driver.  
HOMEWORK: UK to improve the wording

~~5.6.1.2.4. The activated system shall at any time prior and after a lane change manoeuvre ensure that the vehicle does not cross any lane marking, when tested in the conditions defined in Annex 7, paragraph 3.1.1 (EU1 test) a safe lateral distance to other road users. The vehicle manufacturer shall provide documentation about how such a safe distance is achieved to the technical service.~~

5.6.1.2.5. If the activated ACSF detects that due to a sudden unexpected event the vehicle is in imminent danger to collide with another road user ahead or beside the vehicle and that the time for a safe transition procedure is too short, an emergency manoeuvre shall be carried out (e.g. by braking the vehicle and/or by steering).

Kommentiert [OK11]: § moved to 5.6.1.6

Kommentiert [AL212]: moved at the beginning at the section

#### Driver involvement detection

5.6.1.2.5. The system shall detect ~~if the driver's seatbelt is becomes unfastened, a transition demand of [4s] shall be initiated~~. ~~When the driver's seatbelt is detected to be unfastened a transition demand shall be initiated according to 5.6.1.4.4.~~

#### 5.6.1.2.6. Driver availability recognition system

The system shall comprise a driver availability recognition system that is active whenever the ACSF system is active.

The driver availability recognition system shall detect that the driver is present in the driver seat and that he is available to take over the steering.

#### 5.6.1.2.6.1. Driver not present in the driver seat

~~When if the driver is not present in the driver seat, the system shall provide a distinctive warning until the driver is detected to be back in the driver seat or until a transition demand of [15s] shall be initiated.~~

~~When the driver is not back in the driver seat during the distinctive warning with a max. duration of [15 s] a transition demand shall be initiated according to 5.6.1.4.3.~~

Kommentiert [OK13]: now separation between presence and availability for clarification

Kommentiert [AL214]: emergency manoeuvre?

#### 5.6.1.2.6.2. Driver not available to take over the steering

The system shall check if the driver is available to take over the steering by permanently evaluating driver's driving activity. The means to detect driver's activity [(e.g. head and/or eye movement and/or input to any control element of the vehicle)] shall be selected by the manufacturer.

When the driver does not show any driving activity for a time span of maximum [153] min ~~When the driver is not available the system shall provide a distinctive warning until appropriate actions of the driver are detected (e.g. the driver resumes manual control) or until a transition demand of [15 s] is shall be initiated.~~

~~When the system does not detect appropriate actions from the driver during the distinctive warning with a max. duration of [15 s] a transition demand shall be initiated~~

~~according to 5.6.1.4.3.~~

~~5.6.1.4.1. If the system detects that its boundaries are reached or will be reached shortly or in case of a system failure it shall provide a transition demand.~~

### 5.6.1.3. System information data

Kommentiert [AL215]: Move 5.6.1.3 after 5.6.1.8.5

- 5.6.1.3.1. Following data shall be provided together with the documentation package required in Annex 6 of this regulation to the Technical Service at the time of type approval
- 5.6.1.3.1.1. The values for  $V_{smax}$ ,  $V_{smin}$  and  $a_{ysmax}$ .
- 5.6.1.3.1.2. The conditions under which the system can be activated, i. e. when the conditions for operation of the system are fulfilled.
- 5.6.1.3.1.3. Information about system boundaries at which the activated system shall issue a transition demand.
- 5.6.1.3.1.4. The specific values for time according to 5.6.1.4.2 which are foreseen for safe transition to manual steering under different circumstances.
- 5.6.1.3.1.5. Documentation about the chosen strategies regarding the minimal risk manoeuvre which is foreseen depending on the given traffic situation.
- 5.6.1.3.1.6. Documentation about the chosen strategies regarding the emergency manoeuvre which is foreseen in different sudden critical events.
- 5.6.1.3.1.7. Information about ~~how~~ the driver availability recognition system:  
- how it detects the presence of the driver in the seat and  
- how it detects driver availability to take over the steering and  
- how it evaluates driver's activity and  
- how it detects appropriate driver activities after a distinctive warning
- 5.6.1.3.1.8. Information about how the failure warning signal status and the confirmation of the valid software version can be checked via the use of an electronic communication interface.
- 5.6.1.3.1.9. Documentation about which system software version is valid. This documentation shall be updated whenever a software version was amended.
- 5.6.1.4. Transition demand ~~and transition procedure and system operation during transition~~
- ~~5.6.1.4.1. If the system detects that its boundaries are reached or will be reached shortly or in case of a system failure it shall provide a transition demand.~~
- 5.6.1.4.2. The timing of the transition demand shall be such that sufficient time is provided for a safe transition to manual steering.

5.6.1.4.2.1. In case of normal operation operating conditions and in case that the system has the information that system boundaries will be reached in 4 s including the following cases:

- if the speed of the vehicle with activated ACSF exceeds  $v_{smax}$ , or
- if the vehicle with activated ACSF reaches a lateral acceleration of more than  $a_{vsmax}$ , or
- if a system boundary is reached due to a missing lane marking, or

a transition demand of 4 second shall be given not later than 4 s before system boundaries are reached initiated and the system shall follow the initial path and shall not cross any lane marking for at least 4 s.

5.6.1.4.2.2. In case of a sudden unexpected event with imminent danger of a collision a transition demand shall be given immediately and an emergency manoeuvre shall be initiated.

5.6.1.4.2.3. In case of a single sensor failure occurs a sudden unexpected event without imminent danger of a collision a transition demand shall be given immediately and the system shall follow the initial path and shall not cross any lane marking for at least [4 s] after the transition demand, in the following cases

- if the speed of the vehicle with activated ACSF exceeds  $v_{smax}$ , or
- if the vehicle with activated ACSF reaches a lateral acceleration of more than  $a_{vsmax}$ , or
- if a system boundary is reached due to a missing lane marking, or
- if a single sensor failure occurs.

5.6.1.4.3. If a transition demand is given because a driver availability recognition system has detected that the driver is to be inattentive not present in his seat and/or is not available to take over the steering although a warning to restore attentiveness was provided to the driver and if a transition demand shall be is given, the system shall not cross any lane marking for at least [4 s] after the transition demand.

a transition demand shall be given immediately and the system shall follow the initial path and shall not cross any lane marking for at least 4 s.

5.6.1.4.4. The system shall provide a transition demand if the driver's seatbelt is unfastened or if the driver's seat is left by the driver. In this case the system shall not cross any lane marking for follow the initial path at least [4 s] after the transition demand.

5.6.1.4.5. In case of other failures than a single sensor failure a transition demand shall be given immediately [for 4 s] and the system shall initiate the fail-safe strategy as declared by the manufacturer in Annex 6 of this regulation, as soon as the failure is detected.

**Kommentiert [OK16]:** normal operating conditions now defined in § 2.4.8.7; clarified that here the system boundaries are foreseeable for the system

**Kommentiert [AL217]:** same case as 5.6.1.4.2.1

**Formatiert:** Einzug: Erste Zeile: 0 cm

**Kommentiert [OK18]:** if a lane marking is missing or if the sensor cannot detect a marking anymore, only to follow the path can be required

**Formatiert:** Durchgestrichen

**Kommentiert [AL219]:** Tob e deleted. covered by 5.6.1.6.1

**Formatiert:** Durchgestrichen

**Kommentiert [OK20]:** if a lane marking is missing or if the sensor cannot detect a marking anymore, only to follow the path can be required

**Formatiert:** Standard, Einzug: Links: 0 cm, Hängend: 2,49 cm, Keine Aufzählungen oder Nummerierungen

**Kommentiert [AL221]:** same case as 5.6.1.4.2.1

**Formatiert:** Einzug: Links: 0 cm, Hängend: 2,49 cm, Abstand Nach: 10 Pt.

**Kommentiert [OK22]:** if a lane marking is missing or if the sensor cannot detect a marking anymore, only to follow the path can be required

**Kommentiert [OK23]:** leaving driver's seat already covered by availability recognition, item presence detection, and § 5.6.1.4.3

**Kommentiert [AL224]:** definition?

**Formatiert:** Hervorheben

**Formatiert:** Hervorheben

**Kommentiert [AL225]:** to be moved to section 5.6.1.2

~~5.6.1.4.6. In case the vehicle is fitted with a built-in infotainment system, content visible to the driver, which is not relevant for driving, shall be deactivated as long as a transition demand is issued.~~

5.6.1.4.7. The transition demand shall be provided by a visual warning signal and either an acoustic warning signal or by imposing a haptic warning signal. The warning shall be escalating with time in terms of enlarging the intensity of the warning and/or in terms of adding and/or changing the warning means, or start immediately with the highest intensity level.

5.6.1.4.6. In case the vehicle is fitted with a built-in infotainment system, content visible to the driver, which is not relevant for driving, shall be deactivated as long as a transition demand is issued.

5.6.1.4.8 the vehicle shall not cross any lane marking during the transition demand

5.6.1.5. Minimal Risk Manoeuvre

5.6.1.5.1. If the system detects that after a transition demand the driver does not take over manual control of the steering again the vehicle shall carry out a minimum risk manoeuvre ~~not later than 4 s after the start of the transition demand.~~ Alternatively the minimal risk manoeuvre may start at the beginning of the transition demand.

5.6.1.5.2. It shall at any time be possible for the driver to override the minimal risk manoeuvre by the driver. The system may be designed to exclude unintended override.

5.6.1.5.3. ~~Not later than 4 s after~~ With the start of the minimal risk manoeuvre the hazard lights shall be activated automatically. Additionally, an acoustic warning device may be permitted to warn the other road users.

5.6.1.6. Emergency Manoeuvre

5.6.1.6.1. ~~If the activated ACSF detects that due to a sudden unexpected event the vehicle is in imminent danger to collide with another road user ahead or beside the vehicle and that the time for a safe transition procedure is too short, an emergency manoeuvre shall be carried out (e.g. by braking the vehicle and/or by steering).~~

5.6.1.7. Longitudinal control and protective Braking deceleration

5.6.1.7.1. Any vehicle equipped with an ACSF of category E shall be able to control the longitudinal speed of the vehicle ~~meet the following requirements for protective braking.~~ (Characteristics?)

5.6.1.7.1.1. If the activated system detects that the distance to other road users in front is less or will shortly be less than the foreseen safety distance a protective deceleration braking shall be carried out until the foreseen safety distance is reached again.

5.6.1.7.1.2. If the activated system detects that due to a sudden unexpected event the vehicle is in imminent danger to collide with another road user in front and that the time for a safe transition procedure is too short, a protective braking deceleration as emergency manoeuvre shall be carried out. Only in case a lane change can be carried out safely, alternatively a lane change manoeuvre can be carried out to prevent the collision.

Kommentiert [AL226]: Needed.?general case covers this.

Kommentiert [OK27]: if we allow to start with an MRM already with the beginning of the transition demand (as reasonably stated in § 5.6.1.5.1), hazard warning lights should not be required immediately in order to avoid excessive flashing of hazard lights even if there is no imminent danger or real critical situation

Kommentiert [AL228]: description of the emergency manoeuvre to be put here.

Kommentiert [AL229]: same as 5.6.1.7.1.1.

Kommentiert [AL230]:

Kommentiert [AL231]: definition

5.6.1.7.1.3. The protective **braking deceleration** must be able to deliver full braking force of the vehicle in order to achieve a **maximum deceleration**.

Kommentiert [AL232]: WHICH ONE?

#### ✚ 5.6.1.8. Data Storage System for ACSF (DSSA)

[ 5.6.1.8.1. The DSSA shall record and store the data during the operation of the ACSF system for situations of driving, ACSF status, the failure, and the driver's operation in order to demonstrate that if the ACSF had operated properly in align with the relevant requirements, when a vehicle fitted with Advanced Driver Assistance Steering System having ACSF is involved in case of a road accident. ~~[A video signal that is monitoring the driver shall be included in the recorded data.]~~ The DSSA shall be fitted in the vehicle and should not contain any radio interface. The DSSA shall be designed to ensure data security and data protection and shall be protected against tampering and misuse. The driver and the passengers of the vehicle have to be adequately informed about the data capture. Principally, they shall be enabled to decide by themselves by several options about the processing of the data.

5.6.1.8.2 The DSSA shall record and store following data:

- GPS-time
- GPS Location
- Information about the ACSF status
- Information about failures
- Information about transition demands
- Information about minimal risk manoeuvre
- Takeover of the steering by the driver

~~[5.6.1.8.2. It shall be possible that the drivers may switch off the function of recording video signal by driver's intention.]~~

5.6.1.8.3. The recorded data shall not be deletable and not be volatilized in the DSSA without any deterioration [for at least [6] month].

5.6.1.8.4. If ~~The special tools~~ are necessary to get access to recorded data, the tools shall be made available ~~specified by the manufacturer~~ to the authorities, the driver and the passengers of the vehicle and the vehicle owner.

5.6.1.8.5. The DSSA shall record at least for [305] seconds prior to and [110] second(s) ~~after an accident.~~

**Kommentiert [OK33]:** As DSSA is also regulated in Cat. B2, and if the group agrees that Cat E is only permitted in combination with Cat. B2, the DSSA paragraphs could be deleted here.

#### 5.6.2. Special Provisions for ACSF of Category D

Any system of Category D ACSF shall fulfill the following requirements.

##### 5.6.2.1. General

5.6.2.1.1. The system shall be active (deliver automatic steering) only after a deliberate action of the driver and if the conditions for operation of the system are fulfilled (all associated functions – e.g. brakes, accelerator, steering, camera/radar/lidar etc. are working properly).

- 5.6.2.1.2. The vehicle shall be equipped with a means for the driver to activate and deactivate the system. The deactivation shall be possible at any time.
- 5.6.2.1.3. Steering by the driver shall override steering by the system. Braking or accelerating by the driver shall override speed selection by the system.
- 5.6.2.1.4. The specified maximum speed  $V_{smax}$  shall not have a value of more than 130 km/h
- 5.6.2.1.5. The specified maximum lateral acceleration  $a_{ysmax}$  shall not have a value of more than 3 m/s<sup>2</sup> and of less than 1 m/s<sup>2</sup>.
- 5.6.2.1.6. The activated system shall at any time control the movement of the vehicle in such a way that the vehicle does not induce any safety critical situations and that the movements of the vehicle are clear to other road users.
- 5.6.2.1.7. The system status shall be indicated to the driver by a visual signal.
- The indication shall [at least] distinguish between the system status stand-by Mode, active Mode and failure Mode.
- The indication shall be present as long as the relevant system status persists.
- When the system is switched off by the driver, the indication of stand-by Mode and failure Mode may be suppressed.
- Any change in system status shall be indicated by a visual and either an acoustic or haptic signal.
- 5.6.2.1.8. The vehicle shall be equipped with means to monitor at any time when ACSF is active a minimum range to the front ( $S_{Front}$ ), to the right ( $S_{side}$ ), and to the left side ( $S_{side}$ ) and behind ( $S_{Rear}$ ) the vehicle with the purpose to avoid or to mitigate collisions.
- 5.6.2.1.8.1. The minimal range in front ( $S_{Front}$ ) of the ACSF vehicle shall be calculated according to the following formula:
- $$S_{Front} = V_{ACSF}^2 / (2 \cdot a_{ACSF})$$
- where:
- $S_{Front}$  = relative distance between the vehicle equipped with ACSF and the vehicle driving in front, measured in meters from the front edge of the vehicle equipped with ACSF to the rear end of the vehicle driving in front.
- $V_{ACSF}$  = speed of the vehicle equipped with ACSF measured in m/s
- $a_{ACSF}$  = 3,7 m/s<sup>2</sup> = feasible deceleration under wet conditions
- 5.6.2.1.8.2. The minimal range to the rear ( $S_{Rear}$ ) of the ACSF vehicle shall be calculated according to the following formula:
- $$S_{Rear} = d_{reaction, rear} + d_{brake, rear} + d_{safety, rear}$$

**with:**

$$d_{reaction, rear} = (v_{rear} - v_{VUT}) * t_{reaction}$$

$$d_{brake, rear} = \frac{(v_{rear} - v_{ACSF})^2}{2 * a_{brake}}$$

$$d_{safety, rear} = v_{ACSF} * t_d$$

**where:**

$S_{Rear}$  = relative distance between the vehicle equipped with ACSF and the vehicle behind, measured in meters from the rear edge of the vehicle equipped with ACSF to the front end of the vehicle behind.

$d_{reaction, rear}$  = relative distance of the vehicle driving behind the vehicle equipped with ACSF caused by the reaction of the driver to brake, measured in meters

$t_{reaction}$  = 1,2 s = reaction time of the driver driving the vehicle behind the vehicle equipped with ACSF needed to execute the braking and to built up the full braking force, measured in seconds

$d_{brake, rear}$  = braking distance of the vehicle driving behind the vehicle equipped with ACSF, measured in meters

$d_{safety, rear}$  = safety distance between the vehicle equipped with ACSF and the vehicle driving behind, measured in meters

$t_d$  = 1,0 s = safety time gap to vehicle equipped with ACSF after braking, measured in seconds

$v_{rear}$  = [36,1 m/s] speed of the vehicle driving behind the vehicle equipped with ACSF, measured in m/s.

$v_{VUT}$  = speed of the vehicle equipped with ACSF, measured in m/s.

$a_{brake}$  = 3 m/s<sup>2</sup> = admissible deceleration of the vehicle driving behind the vehicle equipped with ACSF

5.6.2.1.8.3. The minimal range to the left and to the right (side) shall be at least 7 m (measured from the medium longitudinal centerline of the vehicle equipped with ACSF)

5.6.1.1.9. The vehicle shall fulfill the tests for Category D, i.e. FU1, FU2, FU3, TR1, TR2, TR3, TR4, TR5, EM1 and EM2, as specified in Annex 7.

5.6.2.2. Operation of ACSF

5.6.2.2.1. Any lane change manoeuvre shall be indicated only if:

- the vehicle is travelling on a road section which is not dedicated to pedestrians or bicyclists and which has a [physical or constructional] separation of traffic moving in opposite directions and which has at least two lanes for the direction the vehicle is driving and

- any traffic that can affect the safe manoeuvre is identified by equipment installed on the vehicle and

- the vehicle equipment can analyze speed and distance of the identified traffic to ensure a safe manoeuvre (e.g. does not cause a deviation to the flow, direction of other traffic or considering left- or right-hand traffic).

- 5.6.2.2.2. If a lane change manoeuvre is carried out, the correspondent direction indicator lamps shall be automatically activated minimum 3 s
- a) prior to the start of the lane change manoeuvre or
  - b) prior the vehicle has touched the lane markings
- 5.6.2.2.3. The lane change manoeuvre shall be completed, except the system detects an imminent critical situation or the system is overridden by the steering of the driver.
- 5.6.2.2.4. The activated system shall prior and after a lane change manoeuvre ensure that the vehicle does not cross any lane marking.
- 5.6.2.2.5. **Detection of unfastening seatbelt**
- The system shall detect if the driver's seatbelt is unfastened. When the driver's seatbelt is detected to be unfastened a transition demand shall be initiated according to 5.6.1.4.4.
- 5.6.2.2.6. **Driver availability recognition system**
- The system shall comprise a driver availability recognition system that is active whenever the ACSF system is active.
- The driver availability recognition system shall detect that the driver is present in the driver seat and that he is available to take over the steering.
- 5.6.2.2.6.1. **Driver not present in the driver seat**
- When the driver is not present in the driver seat the system shall provide a distinctive warning until the driver is detected to be back in the driver seat or until a transition demand is initiated.
- When the driver is not back in the driver seat during the distinctive warning with a max. duration of [15 s] a transition demand shall be initiated according to 5.6.1.4.3.
- 5.6.2.2.6.2. **Driver not available to take over the steering**
- The system shall check if the driver is available to take over the steering by permanently evaluating driver's activity. The means to detect driver's activity [(e.g. head and/or eye movement and/or input to any control element of the vehicle)] shall be selected by the manufacturer.

When the driver does not show any activity for a time span of maximum [15] min the system shall provide a distinctive warning until appropriate actions of the driver are detected (e.g. the driver resumes manual control) or until a transition demand is initiated.

When the system does not detect appropriate actions from the driver during the distinctive warning with a max. duration of [15 s] a transition demand shall be initiated according to 5.6.1.4.3.

#### 5.6.2.3. System information data

5.6.2.3.1. Following data shall be provided together with the documentation package required in Annex 6 of this regulation to the Technical Service at the time of type approval

5.6.2.3.1.1. The values for  $V_{smax}$ ,  $V_{smin}$  and  $a_{ysmax}$ .

5.6.2.3.1.2. The conditions under which the system can be activated, i. e. when the conditions for operation of the system are fulfilled.

5.6.2.3.1.3. Information about system boundaries at which the activated system shall issue a transition demand.

5.6.2.3.1.4. The specific values for time according to 5.6.1.4.2 which are foreseen for safe transition to manual steering under different circumstances.

5.6.2.3.1.5. Documentation about the chosen strategies regarding the minimal risk manoeuvre which is foreseen depending on the given traffic situation.

5.6.2.3.1.6. Documentation about the chosen strategies regarding the emergency manoeuvre which is foreseen in different sudden critical events.

5.6.2.3.1.7. Information about the driver availability recognition system:  
- how it detects the presence of the driver in the seat and  
- how it detects driver availability to take over the steering and  
- how it evaluates driver's activity and  
- how it detects appropriate driver activities after a distinctive warning

5.6.2.3.1.8. Information about how the failure warning signal status and the confirmation of the valid software version can be checked via the use of an electronic communication interface.

5.6.2.3.1.9. Documentation about which system software version is valid. This documentation shall be updated whenever a software version was amended.

#### 5.6.2.4. Transition demand and system operation during transition

5.6.2.4.1. If the system detects that its boundaries are reached or will be reached shortly or in case of a system failure it shall provide a transition demand.

5.6.2.4.2. The timing of the transition demand shall be such that sufficient time is provided for a safe transition to manual steering.

- 5.6.2.4.2.1 In case of normal operating conditions and in case that the system has the information that system boundaries will be reached a transition demand shall be given not later than 4 s before system boundaries are reached.
- 5.6.2.4.2.2 In case of a sudden unexpected event with imminent danger of a collision a transition demand shall be given immediately and an emergency manoeuvre shall be initiated.
- 5.6.2.4.2.3 In case of a sudden unexpected event without imminent danger of a collision a transition demand shall be given immediately and the system shall follow the initial path for at least [4 s] after the transition demand, in the following cases
- if the speed of the vehicle with activated ACSF exceeds  $v_{smax}$ , or
  - if the vehicle with activated ACSF reaches a lateral acceleration of more than  $a_{ysmax}$ , or
  - if a system boundary is reached due to a missing lane marking, or
  - if a single sensor failure occurs.
- 5.6.2.4.3. If a transition demand is given because a driver availability recognition system has detected that the driver is not present in his seat and/or is not available to take over the steering, the system shall not cross any lane marking for at least [4 s] after the transition demand.
- 5.6.2.4.4. The system shall provide a transition demand if the driver's seatbelt is unfastened. In this case the system shall not cross any lane marking for at least [4 s] after the transition demand.
- 5.6.2.4.5. In case of other failures than a single sensor failure a transition demand shall be given immediately and the system shall initiate the fail-safe strategy as declared by the manufacturer in Annex 6 of this regulation, as soon as the failure is detected.
- 5.6.2.4.6. In case the vehicle is fitted with a built-in infotainment system, content visible to the driver, which is not relevant for driving, shall be deactivated as long as a transition demand is issued.
- 5.6.2.4.7. The transition demand shall be provided by a visual warning signal and either an acoustic warning signal or by imposing a haptic warning signal. The warning shall be escalating with time in terms of enlarging the intensity of the warning and/or in terms of adding and/or changing the warning means, or start immediately with the highest intensity level.
- 5.6.2.5. Minimal Risk Manoeuvre
- 5.6.2.5.1. If the system detects that after a transition demand the driver does not take over manual control of the steering again the vehicle shall carry out a minimum risk manoeuvre not later than 4 s after the start of the transition demand. Alternatively the minimal risk manoeuvre may start at the beginning of the transition demand.

- 5.6.2.5.2. It shall at any time be possible to override the minimal risk manoeuvre by the driver. The system may be designed to exclude unintended override.
- 5.6.2.5.3. Not later than 4 s after the start of the minimal risk manoeuvre the hazard lights shall be activated automatically. Additionally, an acoustic warning device may be permitted to warn the other road users.
- 5.6.2.6. Emergency Manoeuvre
- 5.6.2.6.1. If the activated ACSF detects that due to a sudden unexpected event the vehicle is in imminent danger to collide with another road user ahead or beside the vehicle and that the time for a safe transition procedure is too short, an emergency manoeuvre shall be carried out (e.g. by braking the vehicle and/or by steering).
- 5.6.2.7. Longitudinal control and protective deceleration
- 5.6.2.7.1. Any vehicle equipped with an ACSF of category D shall be able to control the longitudinal speed of the vehicle.
- 5.6.2.7.1.1. If the activated system detects that the distance to other road users in front is less or will shortly be less than the foreseen safety distance a protective deceleration shall be carried out until the foreseen safety distance is reached again.
- 5.6.2.7.1.2. If the activated system detects that due to a sudden unexpected event the vehicle is in imminent danger to collide with another road user in front and that the time for a safe transition procedure is too short, a protective deceleration as emergency manoeuvre shall be carried out. Only in case a lane change can be carried out safely, alternatively a lane change manoeuvre can be carried out to prevent the collision.
- 5.6.2.7.1.3. The protective deceleration must be able to deliver full braking force of the vehicle in order to achieve a maximum deceleration.
- 5.6.3. Special Provisions for ACSF of Category C
- Any system of Category C ACSF shall fulfill the following requirements.
- 5.6.3.1. General
- 5.6.3.1.1. The system shall be active (deliver automatic steering) only after a deliberate action of the driver and if the conditions for operation of the system are fulfilled (all associated functions – e.g. brakes, accelerator, steering, camera/radar/lidar etc. are working properly).
- 5.6.3.1.2. The vehicle shall be equipped with a means for the driver to activate and deactivate the system. The deactivation shall be possible at any time.
- 5.6.3.1.3. Steering by the driver shall override steering by the system. Braking or accelerating by the driver shall override speed selection by the system.
- 5.6.3.1.4. The specified maximum lateral acceleration  $a_{y_{\text{max}}}$  shall not have a value of more than  $3 \text{ m/s}^2$  and of less than  $1 \text{ m/s}^2$ .

- 5.6.3.1.5. The activated system shall at any time control the movement of the vehicle in such a way that the vehicle does not induce any safety critical situations and that the movements of the vehicle are clear to other road users.
- 5.6.3.1.6. The system status shall be indicated to the driver by a visual signal.
- The indication shall [at least] distinguish between the system status stand-by Mode, active Mode and failure Mode.
- The indication shall be present as long as the relevant system status persists.
- When the system is switched off by the driver, the indication of stand-by Mode and failure Mode may be suppressed.
- Any change in system status shall be indicated by a visual and either an acoustic or haptic signal.
- 5.6.3.1.7. The vehicle shall fulfill the tests for Category EC, i.e. FU1 and FU3, as specified in Annex 7. The test FU3 shall only be carried out until a single lane change was completed. Returning into the initial lane is not required.
- 5.6.3.2. Operation of ACSF
- 5.6.3.2.1. Any lane change manoeuvre shall be initiated only if commanded by a deliberate action of the driver (e.g. by using the direction indicator lever for at least 2 s).
- 5.6.3.2.2. If a lane change manoeuvre is carried out, the correspondent direction indicator lamps shall be automatically activated minimum 3 s
- a) prior to the start of the lane change manoeuvre or
  - b) prior the vehicle has touched the lane markings
- 5.6.3.2.3. The lane change manoeuvre shall be completed, except the system detects an imminent critical situation or the system is overridden by the steering of the driver.
- 5.6.3.2.4. The activated system shall prior and after a lane change manoeuvre ensure that the vehicle does not cross any lane marking.
- 5.6.3.3. System information data
- 5.6.3.3.1. Following data shall be provided together with the documentation package required in Annex 6 of this regulation to the Technical Service at the time of type approval
- 5.6.3.3.1.1. The values for  $V_{smax}$ ,  $V_{smin}$  and  $a_{ysmax}$ .
- 5.6.3.3.1.2. The conditions under which the system can be activated, i. e. when the conditions for operation of the system are fulfilled.
- 5.6.3.3.1.3. Information about how the failure warning signal status and the confirmation of the valid software version can be checked via the use of an electronic communication interface.

5.6.3.3.1.4. Documentation about which system software version is valid. This documentation shall be updated whenever a software version was amended.

#### 5.6.4. Special Provisions for ACSF of Category B2

Any system of Category B2 ACSF shall fulfill the following requirements.

##### 5.6.4.1. General

5.6.4.1.1. The system shall be active (deliver automatic steering) only after a deliberate action of the driver and if the conditions for operation of the system are fulfilled (all associated functions – e.g. brakes, accelerator, steering, camera/radar/lidar etc. are working properly).

5.6.4.1.2. The vehicle shall be equipped with a means for the driver to activate and deactivate the system. The deactivation shall be possible at any time.

5.6.4.1.3. Steering by the driver shall override steering by the system. Braking or accelerating by the driver shall override speed selection by the system.

5.6.4.1.4. The specified maximum speed  $v_{smax}$  shall not have a value of more than 130 km/h

5.6.4.1.5. The specified maximum lateral acceleration  $a_{y_{smax}}$  shall not have a value of more than 3 m/s<sup>2</sup> and of less than 1 m/s<sup>2</sup>.

5.6.4.1.6. The activated system shall at any time control the movement of the vehicle in such a way that the vehicle does not induce any safety critical situations and that the movements of the vehicle are clear to other road users.

5.6.4.1.7. The system status shall be indicated to the driver by a visual signal.

The indication shall [at least] distinguish between the system status stand-by Mode, active Mode and failure Mode.

The indication shall be present as long as the relevant system status persists.

When the system is switched off by the driver, the indication of stand-by Mode and failure Mode may be suppressed.

Any change in system status shall be indicated by a visual and either an acoustic or haptic signal.

5.6.4.1.8. The vehicle shall be equipped with means to monitor at any time when ACSF is active a minimum range to the front ( $s_{Front}$ ), to the right ( $s_{side}$ ), and to the left side ( $s_{side}$ ) with the purpose to avoid or to mitigate collisions.

5.6.4.1.8.1. The minimal range in front ( $s_{Front}$ ) of the ACSF vehicle shall be calculated according to the following formula:

$$s_{Front} = v_{ACSF}^2 / (2 \cdot a_{ACSF})$$

where:

$S_{Front}$  = *relative distance between the vehicle equipped with ACSF and the vehicle driving in front, measured in meters from the front edge of the vehicle equipped with ACSF to the rear end of the vehicle driving in front.*

$V_{ACSF}$  = *speed of the vehicle equipped with ACSF measured in m/s*

$a_{ACSF}$  = *3,7 m/s<sup>2</sup> = feasible deceleration under wet conditions*

5.6.4.1.9. The vehicle shall fulfill the tests for Category B2, i.e. FU1, TR1, TR2, TR3, TR4, TR5, EM1 and EM2, as specified in Annex 7.

5.6.4.2. Operation of ACSF

5.6.4.2.1. The ACSF system of category B2 shall only operate if:

- the vehicle is travelling on a road section which is not dedicated to pedestrians or bicyclists and which has a [physical or constructional] separation of traffic moving in opposite directions
- any traffic that can affect the safe keeping of the vehicle in the lane is identified by equipment installed on the vehicle and
- the vehicle equipment can analyze speed and distance of the identified traffic to ensure a safe lane keeping (e.g. does not cause a deviation to the flow, or direction of other traffic).

5.6.4.2.2. The activated system shall at any time ensure that the vehicle does not cross any lane marking.

5.6.4.2.3. The system shall detect if the driver's seatbelt is unfastened. When the driver's seatbelt is detected to be unfastened a transition demand shall be initiated according to 5.6.1.4.4.

5.6.4.2.4. Driver availability recognition system

The system shall comprise a driver availability recognition system that is active whenever the ACSF system is active.

The driver availability recognition system shall detect that the driver is present in the driver seat and that he is available to take over the steering.

5.6.4.2.4.1. When the driver is not present in the driver seat the system shall provide a distinctive warning until the driver is detected to be back in the driver seat or until a transition demand is initiated.

When the driver is not back in the driver seat during the distinctive warning with a max. duration of [15 s] a transition demand shall be initiated according to 5.6.1.4.3.

#### 5.6.4.2.4.2 Driver not available to take over the steering

The system shall check if the driver is available to take over the steering by permanently evaluating driver's activity. The means to detect driver's activity [(e.g. head and/or eye movement and/or input to any control element of the vehicle)] shall be selected by the manufacturer.

When the driver does not show any activity for a time span of maximum [15] min the system shall provide a distinctive warning until appropriate actions of the driver are detected (e.g. the driver resumes manual control) or until a transition demand is initiated.

When the system does not detect appropriate actions from the driver during the distinctive warning with a max. duration of [15 s] a transition demand shall be initiated according to 5.6.1.4.3.

#### 5.6.4.3. System information data

5.6.4.3.1. Following data shall be provided together with the documentation package required in Annex 6 of this regulation to the Technical Service at the time of type approval

5.6.4.3.1.1. The values for  $V_{smax}$ ,  $V_{smin}$  and  $a_{ysmax}$ .

5.6.4.3.1.2. The conditions under which the system can be activated, i. e. when the conditions for operation of the system are fulfilled.

5.6.4.3.1.3. Information about system boundaries at which the activated system shall issue a transition demand.

5.6.4.3.1.4. The specific values for time according to 5.6.1.4.2 which are foreseen for safe transition to manual steering under different circumstances.

5.6.4.3.1.5. Documentation about the chosen strategies regarding the minimal risk manoeuvre which is foreseen depending on the given traffic situation.

5.6.4.3.1.6. Documentation about the chosen strategies regarding the emergency manoeuvre which is foreseen in different sudden critical events.

5.6.4.3.1.7. Information about the driver availability recognition system:  
- how it detects the presence of the driver in the seat and  
- how it detects driver availability to take over the steering and  
- how it evaluates driver's activity and  
- how it detects appropriate driver activities after a distinctive warning

5.6.4.3.1.8. Information about how the failure warning signal status and the confirmation of the valid software version can be checked via the use of an electronic communication interface.

5.6.4.3.1.9. Documentation about which system software version is valid. This documentation shall be updated whenever a software version was amended.

- 5.6.4.4. Transition demand and system operation during transition**
- 5.6.4.4.1.** If the system detects that its boundaries are reached or will be reached shortly or in case of a system failure it shall provide a transition demand.
- 5.6.4.4.2.** The timing of the transition demand shall be such that sufficient time is provided for a safe transition to manual steering.
- 5.6.4.4.2.1** In case of normal operating conditions and in case that the system has the information that system boundaries will be reached a transition demand shall be given not later than 4 s before system boundaries are reached.
- 5.6.4.4.2.2** In case of a sudden unexpected event with imminent danger of a collision a transition demand shall be given immediately and an emergency manoeuvre shall be initiated.
- 5.6.4.4.2.3** In case of a sudden unexpected event without imminent danger of a collision a transition demand shall be given immediately and the system shall follow the initial path for at least [4 s] after the transition demand, in the following cases
- if the speed of the vehicle with activated ACSF exceeds  $v_{smax}$ , OR
  - if the vehicle with activated ACSF reaches a lateral acceleration of more than  $a_{ysmax}$ , OR
  - if a system boundary is reached due to a missing lane marking, or
  - if a single sensor failure occurs.
- 5.6.4.4.3.** If a transition demand is given because a driver availability recognition system has detected that the driver is not present in his seat and/or is not available to take over the steering, the system shall not cross any lane marking for at least [4 s] after the transition demand.
- 5.6.4.4.4.** The system shall provide a transition demand if the driver's seatbelt is unfastened. In this case the system shall not cross any lane marking for at least [4 s] after the transition demand.
- 5.6.4.4.5.** In case of other failures than a single sensor failure a transition demand shall be given immediately and the system shall initiate the fail-safe strategy as declared by the manufacturer in Annex 6 of this regulation, as soon as the failure is detected.
- 5.6.4.4.6.** In case the vehicle is fitted with a built-in infotainment system, content visible to the driver, which is not relevant for driving, shall be deactivated as long as a transition demand is issued.
- 5.6.4.4.7.** The transition demand shall be provided by a visual warning signal and either an acoustic warning signal or by imposing a haptic warning signal. The warning shall be escalating with time in terms of enlarging the intensity of the warning and/or in terms of adding and/or changing the warning means, or start immediately with the highest intensity level.
- 5.6.4.5. Minimal Risk Manoeuvre**

- 5.6.4.5.1. If the system detects that after a transition demand the driver does not take over manual control of the steering again the vehicle shall carry out a minimum risk manoeuvre not later than 4 s after the start of the transition demand. Alternatively the minimal risk manoeuvre may start at the beginning of the transition demand.
- 5.6.4.5.2. It shall at any time be possible to override the minimal risk manoeuvre by the driver. The system may be designed to exclude unintended override.
- 5.6.4.5.3. Not later than 4 s after the start of the minimal risk manoeuvre the hazard lights shall be activated automatically. Additionally, an acoustic warning device may be permitted to warn the other road users.
- 5.6.4.6. Emergency Manoeuvre
  - 5.6.4.6.1. If the activated ACSF detects that due to a sudden unexpected event the vehicle is in imminent danger to collide with another road user ahead or beside the vehicle and that the time for a safe transition procedure is too short, an emergency manoeuvre shall be carried out (e.g. by braking the vehicle and/or by steering within the lane).
- 5.6.4.7. Longitudinal control and protective deceleration
  - 5.6.4.7.1. Any vehicle equipped with an ACSF of category B2 shall be able to control the longitudinal speed of the vehicle.
    - 5.6.4.7.1.1. If the activated system detects that the distance to other road users in front is less or will shortly be less than the foreseen safety distance a protective deceleration shall be carried out until the foreseen safety distance is reached again.
    - 5.6.4.7.1.2. If the activated system detects that due to a sudden unexpected event the vehicle is in imminent danger to collide with another road user in front and that the time for a safe transition procedure is too short, a protective deceleration as emergency manoeuvre shall be carried out.
    - 5.6.4.7.1.3. The protective deceleration must be able to deliver full braking force of the vehicle in order to achieve a maximum deceleration.

#### 5.6.4.8. Data Storage System for ACSF (DSSA)

[5.6.4.8.1. The DSSA shall record and store the data during the operation of the ACSF in order to demonstrate if the ACSF had operated properly in align with the relevant requirements in case of a road accident. The DSSA shall be fitted in the vehicle and should not contain any radio interface. The DSSA shall be designed to ensure data security and data protection and shall be protected against tampering and misuse. The driver and the passengers of the vehicle have to be adequately informed about the data capture. Principally, they shall be enabled to decide by themselves by several options about the processing of the data.

5.6.4.8.2 The DSSA shall record and store following data:

- GPS-time
- GPS Location
- Information about the ACSF status
- Information about failures
- Information about transition demands
- Information about minimal risk manoeuvre
- Takeover of the steering by the driver

5.6.4.8.3. The recorded data shall not be deletable and not be volatilized in the DSSA without any deterioration [for at least [6] month].

5.6.4.8.4. If special tools are necessary to get access to recorded data, the tools shall be made available by the manufacturer to the authorities, the driver and the passengers of the vehicle and the vehicle owner.

5.6.4.8.5. The DSSA shall record at least for [30] seconds prior to and [10] seconds after an accident.]

#### 5.6.5. Special Provisions for ACSF of Category B1

Any system of Category B1 ACSF shall fulfill the following requirements.

##### 5.6.5.1. General

5.6.5.1.1. The vehicle shall be equipped with a means for the driver to activate and deactivate the system. The deactivation shall be possible at any time.

5.6.5.1.2. The system shall be designed so that excessive intervention of steering control (e.g. an excessive steering torque) is suppressed to ensure the steering operability by the driver and to avoid unexpected vehicle behaviour, during its operation.

The end of the intervention shall be such that the LKAS reduces its directional control to zero in a progressive manner, to ensure easy and safe handling of the vehicle, as defined in paragraph 5.1.1. The directional control fade-out strategy shall be at the discretion of the vehicle manufacturer.

The steering control effort necessary to override the directional control provided by the LKAS shall not exceed the value specified in paragraph 6.2.4.2. for an intact steering equipment.

#### 5.6.5.2. Operation of ACSF

5.6.5.2.1 The activated system shall at any time ensure that the vehicle does not cross any lane marking.

5.6.5.2.2 When the LKAS is temporarily not available, for example due to inclement weather conditions, the system shall clearly inform the driver about the system status, except if the system is in the OFF mode, e.g. switched off. This exception does not affect the required warning in the case of a system failure.

5.6.5.2.3 When the system is active (i.e. ready to intervene or intervening), it shall provide a means of detecting that the driver is in control of the vehicle. In the event that the system has detected for a time span of maximum [30] s that the driver is likely to be no longer in control of the vehicle, distinctive warning shall be provided until the driver is detected to be in control of the vehicle again (e.g. via input on the steering wheel, brake pedal actuation) or until the system is deactivated, either automatically or manually.

In the event that the system has detected for a time span of maximum [60] s that the driver is likely to be no longer in control of the vehicle, the system shall be automatically deactivated.

When the system is automatically deactivated, the system shall clearly inform the driver about the system status.

The warning shall be provided by at least two means out of optical, acoustic and haptic given simultaneously or in a cascade.

#### 5.6.5.3. System information data

5.6.5.3.1. Following data shall be provided together with the documentation package required in Annex 6 of this regulation to the Technical Service at the time of type approval

5.6.5.3.1.1. The values for  $V_{smax}$ ,  $V_{smin}$  and  $a_{ysmax}$ .

5.6.5.3.1.2. The conditions under which the system can be activated, i. e. when the conditions for operation of the system are fulfilled.

5.6.5.3.1.3. Information about the driver availability recognition system:  
- how it detects that the driver is in control of the vehicle

5.6.5.3.1.4. Information about how the failure warning signal status and the confirmation of the valid software version can be checked via the use of an electronic communication interface.

**5.6.5.3.1.5** Documentation about which system software version is valid. This documentation shall be updated whenever a software version was amended.

**5.6.6. Special Provisions for ACSF of Category A**

- to be developed based on the requirements for a Category 5 system-

**Annex 7**

**Text requirements for automatically commanded steering functions**

**1. General Provisions**

Vehicles fitted with ACSF shall fulfill the tests requirements of this annex according to the corresponding category of ACSF specified in Table 1.

**2. Test conditions**

**2.1.** The test shall be performed on a flat, dry asphalt or concrete surface delivering good adhesion. The ambient temperature shall be between 0° C and 45° C.

**2.2. Lane markings**

The lane markings and the width of the lane used in the tests shall be those of one of the Contracting Parties, with the markings being in good condition and of a material conforming to the standard for visible lane markings of that Contracting Party. The lane marking layout used for the testing shall be recorded.

The test shall be performed under visibility conditions that allow safe driving at the required test speed.

**2.3. Tolerances**

All vehicle speeds specified in the tests shall be met with a tolerance of  $\pm 2$  km/h.

**2.4. Target vehicle**

The target vehicle shall be a high volume series production passenger car of category M1 AA saloon<sup>1</sup> or in the case of a soft target an object representative of such a vehicle in terms of its detection characteristics. A soft target is a target that will suffer minimum damage and cause minimum damage to the subject vehicle in the event of a collision.

**3. Tests**

Table 1 specifies which tests have to be fulfilled by each ASCF category.

Test \ ACSF category	A	B1	B2	C	D	E
Fu1 Lane keeping		tbd	tbd	tbd	tbd	x
Fu2 Abort of Lane change				tbd	tbd	x
Fu3 Lane change				tbd	tbd	x
Tr1 Lateral acc.		tbd	tbd	tbd	tbd	x

<sup>1</sup> As defined in the Consolidated Resolution on the Construction of Vehicles (R.E.3.), document ECE/TRANS/WP.29/78/Rev.2, para. 2

Tr2 Missing marking		tbd	tbd	tbd	tbd	x
Tr3 Driver <del>not available</del> unfastened		tbd	tbd	tbd	tbd	x
Tr4 Failure		tbd	tbd	tbd	tbd	x
Tr5 Taking over		tbd	tbd	tbd	tbd	x
EM1 Moving target (decel. 6 m/s <sup>2</sup> )		tbd	tbd	tbd	tbd	x
EM2 Stationary target		tbd	tbd	tbd	tbd	x

Table 1

### 3.1. Functionality Tests

#### 3.1.1. Functionality Test 1 (FU1): Test for lane keeping

3.1.1.1 Drive the vehicle with activated ACSF ~~at least [5 min]~~ on a track with ~~various curvatures~~ with road markings at each side of the lane at ~~various 2~~ different lateral accelerations between 0.5 m/s<sup>2</sup> and 90 % of  $a_{y,max}$  ~~test speeds selected by the technical service up to  $v_{s,max}$  - 10 km/h and down to  $v_{s,min}$ . Repeat each test case. The curvatures of the track lateral accelerations shall be selected such that the at  $v_{s,max}$  lateral accelerations vehicle speed remains in the range from  $v_{s,min}$  up to  $v_{s,max}$  0,5 m/s<sup>2</sup> up to 90 % of  $a_{y,max}$  are achieved.~~

3.1.1.2 ~~Various curvature test~~ Data for the whole lateral acceleration range ~~if the test track which was used for paragraph 3.1.1.1. has no various curvature, Technical service shall require to manufacturer to deliver data about fulfilling test of the various curvature, for lane keeping capabilities for the whole lateral acceleration range.~~

3.1.1.3 The requirements of the test are fulfilled if the vehicle does not cross any lane marking.

#### 3.1.2. Functionality Test 2 (FU2): Test for the abort of lane change

3.1.2.1 Drive the vehicle with activated ACSF on a straight track with at least two lanes with road markings at each side of the lane at a test speed of 70 km/h or ( $v_{s,max}$  - 20 km/h) whatever is lower. Two other vehicles of category M1 or target vehicles shall drive centered in the lane ahead and behind the test vehicle with the same speed. The time gap to the vehicle ahead shall be selected by the test vehicle itself. The time gap to the vehicle behind shall be 1.9 s  $\pm$ 0.1 s. The desired speed of the test vehicle shall then be set such, e.g. 20 km/h higher, that a lane change would be induced to pass the vehicle ahead, however for testing purposes, the execution of the lane change shall be suppressed. The willingness to carry out a lane change ("yes" or "no") shall be recorded. Then a motorcycle of category L3 shall approach from behind on a lane next to the vehicle with a speed of the vehicle test speed plus 50 km/h. ~~The distance time to collision (TTC) (calculated as distance divided by relative speed)~~

between the vehicle and the motorcycle shall be recorded. The motorcycle shall drive with a lateral distance to the lane marking between the motorcycle and the vehicle of  $1\text{ m} \pm 0.25\text{ m}$ .

3.1.2.2 The requirements of the test are fulfilled if:

- the willingness to carry out a lane change changes from "yes" to "no" before the distance TTC between the vehicle and the motorcycle falls below  $68\text{ m}$  and
- the willingness to carry out a lane change remains "no" until the motorcycle has passed the vehicle completely.

3.1.2.3 In case the willingness to carry out a lane change is "no" at any time of the test described in 3.1.2.1 the test shall be repeated without vehicle behind the test vehicle and the requirements for passing the test given in paragraph 3.1.2.2 shall apply.

3.1.2.4 In case the willingness to carry out a lane change is "no" at any time of the test described in 3.1.2.3 the test shall be repeated without vehicle behind the test vehicle and with a motorcycle speed which is successively reduced by  $10\text{ km/h}$  until the willingness to carry out a lane change is "yes" before the functional part of the test. The requirements for passing the test given in paragraph 3.1.2.2 shall apply taking into account the actual motorcycle speed for calculating the appropriate distance value.

Kommentiert [OK34]: Test parameter amended:  $1.9\text{ s}$  now (with  $70\text{ km/h}$  as test speed) correspond to  $37\text{ m}$

Kommentiert [OK35]: Perhaps stating a distance (now  $68\text{ m}$  with  $70\text{ km/h}$  as test speed) is more intuitive than a TTC. Calculation is done with the formula of § 5.6.1.1.8.

### 3.1.3. Functionality Test 3 (FU3): Test for lane change

3.1.3.1 Drive the vehicle with activated ACSF on a straight track with at least two lanes with road markings at each side of the lane at a test speed of 70 km/h or ( $V_{smax} - 20$  km/h) whatever is lower. One vehicle of category M1 or target vehicle shall drive centered in the lane with the same speed. The time gap to the vehicle ahead shall be selected by the test vehicle itself. The desired speed of the test vehicle shall then be set such, e.g. 20 km/h higher, that a lane change would be induced to pass the vehicle ahead.

3.1.3.2. The requirements of the test are fulfilled if:

- the completion of lane change manoeuvre and
- vehicle shall not cross the outer lane marking and
- after the completion of lane change manoeuvre, vehicle shall be back to the initial lane with a time gap of  $1.9\text{ s} \pm 0.1\text{ s}$  to the vehicle behind.

### 3.2. Transition Tests

3.2.1. Transition Test 1 (TR1): Transition due to exceeding lateral acceleration

3.2.1.1. Drive the vehicle with activated ACSF on a track with road markings at each side of the lane at a test speed of 80 km/h or 10 km/h below  $V_{smax}$  whatever is lower. The track shall comprise a section in which the curvature shall be such that at test speed the lateral acceleration of the vehicle would be more than  $(a_{y_{smax}} + 0.5)\text{ m/s}^2$  or  $3.5\text{ m/s}^2$  whatever is lower for a length of at least 150 m. The test driver of the vehicle shall not take over steering control again until the minimal risk maneuver is finished.

3.2.1.2. The requirements of the test are fulfilled if

3.2.1.2.1. In case transitional demand initiated during test

- the transition demand was given not later than at least when the lateral acceleration exceeds  $a_{y_{smax}}$  by more than  $0.3\text{ m/s}^2$  and
- the vehicle does not cross any lane marking for 4 s after the transition demand and
- the minimal risk manoeuvre as specified by the vehicle manufacturer was initiated not later than at least 4 s after the transition demand and
- the hazard lights are activated not later than at least 4 s after the start of the minimal risk manoeuvre transition demand.

3.2.1.2.2. In case no transitional demand during test

- when transition demand was not initiated during test, the vehicle reduces speed by itself so that  $a_{y_{smax}}$  was not exceeded for more than 1 s and vehicle shall not cross any lane marking.

3.2.2. Transition Test 2 (TR2): Transition due to missing lane marking

3.2.2.1. Drive the vehicle with activated ACSF on a track with road markings at each side of the lane at a test speed of 80 km/h or 10 km/h below  $V_{smax}$  whatever is lower. The track shall comprise

Kommentiert [OK36]: UK proposed "not later than" instead of "at least" as better wording

Kommentiert [OK37]: see remark in § 5.6.1.5 with regard to excessive flashing

a section with a length of at least 150 m in which the outer side lane marking is missing on one side and in which the curvature shall be such that at test speed the lateral acceleration of the vehicle would be less than  $a_{y_{\text{smax}}}$  and more than  $0.5 \text{ m/s}^2$ . The test driver of the vehicle shall not take over steering control again until the minimal risk manoeuvre is finished.

3.2.2.2. The requirements of the test are fulfilled if:

3.2.2.2.1. In case transitional demand initiated during test

- the transition demand was given at the latest when the vehicle entered the section with missing lane marking and
- the vehicle does not cross any lane marking for 4 s after the transition demand and
- the vehicle stays in the initial path for 4 s after the transition demand and
- the minimal risk manoeuvre as specified by the vehicle manufacturer was initiated at the latest 4 s after the transition demand and
- the hazard lights may be activated initiated at the latest at least 4 s after the transition demand, no later as when the MRM has started.
- the hazard lights are activated not later than 4 s after the start of the minimal risk manoeuvre.

Kommentiert [OK38]: moved to § 5.6.1.5.3

3.2.2.2.2. In case no transitional demand during test

The vehicle is following the initial path for the complete section with missing lane marking without crossing the lane marking.]

3.2.3. Transition Tests (TR3): Transition due to unfastening the seat belt

3.2.3.1. Drive the vehicle with activated ACSF at least 1 min on a track with curvatures with road markings at each side of the lane at a speed of  $v_{\text{smax}} - 10 \text{ km/h}$ . The curvatures of the track shall be such that at  $v_{\text{smax}}$  lateral accelerations in the range from  $0,5 \text{ m/s}^2$  up to 90 % of  $a_{y_{\text{smax}}}$  are achieved. Subsequently, the driver shall unfasten the seat belt / or the seat belt sensor shall be cut off at the beginning of driving in the curvature.

Kommentiert [OK39]: kind of curvature does not matter for the transition test due to unfastening

3.2.3.2. The requirements of test for transition demand and minimal risk manoeuvre are fulfilled

if :

- the warning signal for transition demand shall be given when the unfastened seat belt was detected according to the paragraph 5.6.1.4.4. The warning signal shall remain exist until the driver operates the steering control and.
- the system shall not cross any lane marking for at least 4 s after the transition demand.
- the vehicle shall initiate one of minimal risk manoeuvre which are described in the system information data not later than 4 s after the start of the transition demand. And the hazard warning signal shall be activated not later than 4 s after the start of the during the control by minimal risk manoeuvre. The minimal risk manoeuvre to be tested is chosen by the car manufacturer and the manoeuvre strategies shall be explained and.

Kommentiert [OK40]: changes in order to make test consistent with § 5.6.1.4.4 and § 5.6.1.5

-When the driver operates the steering control, the minimal risk manoeuvre, activation of hazard warning signal and the warning signal for transition demand shall be deactivated automatically.

Kommentiert [OK41]: Proposal: either delete last bulletpoint here since driver override is tested in TR 5 or include override in TR3 and skip TR 5

#### 3.2.4. Transition Test 4 (TR4): Transition due to failure

3.2.4.1. Drive the vehicle with activated ACSF on a track with road markings at each side of the lane at a test speed of 10 km/h below  $V_{smax}$ . The track shall comprise a section with a length of at least 200 m in which the curvature shall be such that at test speed the lateral acceleration of the vehicle would be less than  $a_{y_{smax}}$  and more than  $0.5 \text{ m/s}^2$ . A single sensor failure [e.g. lane marking detection] of the automatic steering function shall be induced that the vehicle is within the first 50 m of this section, when the transition demand initiated.

3.2.4.2. The requirements of the test are fulfilled if:

- the failure warning and the transition demand were given immediately [not later than at least 0.5 s] after the failure was induced and
- the vehicle does shall not cross any lane marking. By way of derogation from this, the vehicle is allowed to cross a lane marking during a minimum risk manoeuvre if the minimum risk manoeuvre described by the manufacturer foresees a lane change depending on the failure type and the traffic situation; until the minimal risk maneuver initiated and
- the minimal risk manoeuvre as specified by the vehicle manufacturer was initiated at the latest at least 4 s after the transition demand; and
- the hazard lights are may be activated during minimal risk manoeuvre.
- the hazard lights are activated not later than 4 s after the start of the minimal risk manoeuvre.

#### 3.2.5. Transition Test 5 (TR5): Driver take over test

3.2.5.1. Drive the vehicle with activated ACSF on a track with road markings at each side of the lane at a test speed of 70 km/h or ( $V_{smax} - 20 \text{ km/h}$ ) whatever is lower. The track shall comprise a section with a length of at least 200 m in which the curvature shall be such that at test speed the lateral acceleration of the vehicle would be less than  $a_{y_{smax}}$  and more than  $0.5 \text{ m/s}^2$ . A single sensor failure [e.g. lane marking detection] of the automatic steering function shall be induced that the vehicle is within the first 50 m of this section, when the transition demand initiated. The driver shall override the ACSF by steering after the transitional demand and the minimal risk manoeuvre and the hazard warning lights activation were initiated.

3.2.5.2. The requirements of test are fulfilled if the ACSF is deactivated automatically, the minimal risk manoeuvre is aborted and hazard warning signal is deactivated after the driver override the ACSF by steering.

### 3.3. Emergency Tests

#### 3.3.1 Emergency Test 1 (EM1): Protective deceleration braking with moving target

3.3.1.1. Drive the vehicle with activated ACSF behind a target vehicle. The vehicle and the target vehicle shall drive within the lane markings on a track with road markings at each side of the lane at a speed of 70 km/h or ( $V_{\text{max}} - 20$  km/h) whatever is lower. The time gap between the test vehicle and the target vehicle shall be selected by the vehicle itself but shall not be more than 2.4 s  ~~$\pm 0.05$  s~~. Then the target vehicle shall decelerate with  $6 \text{ m/s}^2 \pm 0.25 \text{ m/s}^2$  and with a mean brake jerk of  $6 \text{ m/s}^3 \pm 0.25 \text{ m/s}^3$  in the first second of braking. The vehicle shall not carry out a lane change to avoid a collision. Thus any other lane adjacent to the lane the vehicle is driving in shall be blocked e. g. by other vehicles.

3.3.1.2. The requirements of the test (3.3.1.1.) are fulfilled if the vehicle does not collide with the target vehicle.

#### 3.3.2. Emergency Test 2 (EM2): Protective deceleration braking with stationary target

3.3.2.1. Drive the vehicle with activated ACSF at least 1 min on a track with road markings at each side of the lane at a test speed 10 km/h below  $V_{\text{max}}$ . The vehicle shall approach a target vehicle being at standstill and being placed in the center of the lane. The vehicle shall not carry out a lane change to avoid a collision. Thus any other lane adjacent to the lane the vehicle is driving in shall be blocked e. g. by other vehicles next to the target vehicle.

3.3.2.2. The requirements of the test are fulfilled if the vehicle does not collide with the target vehicle.