



Head restraints: GTR 7 ph2


Test conditions: wording for §6

GTR7-13-XX February, 12th 13th 2013 Target for the dynamic procedure: include in the GTR

o a procedure on a full vehicle

and

 a procedure to perform the test either with a seat on sled or with a body in white at the choice of the manufacturer



- Target for the dynamic procedure: include in the GTR.
 - o a procedure on a full vehicle
 - 6.1. A full vehicle including at least the seat to be tested and all necessary seat and head restraint equipment.

and

- a procedure to perform the test with a seat on sled or with a body in white at the choice of the manufacturer
- 6.2. A seat mounted on the sled and fitted with all necessary attachment hardware, the seat belt system, as well as all necessary equipment for the activation of dynamic head restraints. Alternatively the assessment may be carried out using vehicle body and/or parts sufficient to enable the testing of the seat and head restraint system.

Current GTR7 Text	Munich Text
Strike through indicates deletion	Underline indicates text proposed pre Munich
	Blue text: QICA proposal for February 2013 IG meeting
B. <u>TEXT OF THE REGULATION</u>	
6. TEST CONDITIONS	6. TEST CONDITIONS
The test procedures described in the following	The test procedures described in the following annexes
annexes are to be performed using any or all of the	are to be performed using any or all of the following:
following:	
6.1. A full vehicle including at least the seat to be	6.1. A full vehicle including at least the seat to be tested
tested and all necessary seat and head restraint	and all necessary seat and head restraint equipment.
equipment.	
6.2. A vehicle body in white including at least the	6.2. A vehicle body in white including at least the seat to
seat to be tested and all necessary seat and head	be tested and all necessary seat and head restraint
restraint equipment.	equipment.
6.3. A seat equipped with its head restraint and all	6.23. A seat mounted on the sled equipped with its head
necessary attachment hardware, as well as all	restraint and fitted with all necessary attachment
necessary equipment for the activation of dynamic	hardware, the seat belt system, as well as all necessary
head restraints.	equipment for the activation of dynamic head restraints.
	Alternatively the assessment may be carried out using.
	vehicle body and/or parts sufficient to enable the testing
	of the seat and head restraint system.



Thanks for your attention.