

# SLR "Stage 1"

SLR-24-12

## The complete package

### NEW SIMPLIFIED UN REGULATIONS

- Light Signalling Devices (LSD) → (GRE/2018/02)
  - Road Illumination Devices (RID) → (GRE/2018/03)
  - Retro-Reflective Devices (RRD) → (GRE/2018/04)
- + GRE-79-10  
GRE-79-14

### Transitional Provisions

Coll. Amd. for Regs Nos. 3, 4, 6, 7, 19, 23, 27, 38, 50, 69, 70, 77, 87, 91, 98, 104, 112, 113, 119 and 123  
(GRE/2018/11)

### UPDATED REFERENCES TO DEVICE REGS.

- R48, series 03, 04, 05 and 06 of amendments  
(GRE/2018/30, .../08, .../07, .../06)
  - R53, series 01 and 02 of amendments  
(GRE/2018/17, GRE/2018/15)
  - R74, series 01 of amendments  
(GRE/2018/14)
  - R86, series 00 and 01 of amendments  
(GRE/2018/10, GRE/2018/09)
- + GRE-79-13

### Reorganized and grouped definitions

R48-06, R53-02, R74-01, R86-01  
(GRE/2018/13, GRE-79-08, GRE-79-09, GRE/2018/12)

### Use of "Change Index" and its definition

- R48-06 + Coll. Amd. for R53-02, R74-01 and R86-01  
(GRE/2018/16, GRE/2018/18, GRE-79-11, GRE-79-12)

**All official proposals have been adopted**  
**as amended by the SLR informal documents**

- Only GRE/2018/11 (about TPs) was adopted with square brackets around the 3<sup>rd</sup> paragraph (as requested by EC). This document will be addressed at SLR-24 along with GRE-79-31 and SLR-24-02.
- In GRE-79-13, under A.III section, the "alternative text" in square brackets for Par. 6.3.9. was adopted
- GRE/2018/16 and GRE/2018/18 (Change Index) were adopted as amended by GRE-79-11 but the "Part B" shall read Par. 5.21 instead of Par. 5.19
- Indian informal documents:
  - GRE-79-17/Rev.1 and GRE-79-18/Rev.1 were adopted
  - GRE-79-19 and GRE-79-22 were withdrawn. If necessary India will make a proposal to SLR.

# In addition to the amendments introduced with the SLR informal documents, GRE/2018/03 (RID) was adopted with the following correction:

5.6. Technical requirements concerning cornering lamps (symbol K)

5.6.1. Intensity of light emitted

5.6.1.1. For the left-hand device, the minimum intensity of the light at the specified measuring points shall be as follows:

- a) 2.5D – 30L: 240 cd
- b) 2.5D – 45L: 400 cd
- c) 2.5D – 60L: 240 cd

The same values apply symmetrically for a right-hand device. (Shown in Annex 4 Figure A4-XII)

But Annex 4 figure A4-XII is not on line with the requirements. The horizontal angles in the figures are 60° 45° and 15°  
30°

This shall be 30°

