# CO<sub>2</sub>/FC correction for (N)OVC-HEV/(N)OVC-FCHV

Proposed update by ACEA EV for WLTP SG EV to give the option to avoid unnecessary testing without additional value (updated proposal)

Status: 05.03.2020

### NOVC-HEV/NOVC-FCHV: CO<sub>2</sub>/FC correction

#### Proposal ACEA EV for SG EV (example here based on NOVC-HEV) (status: February 26th)

- ACEA EV is supporting the approach of a generic worst case correction as for pure ICE vehicle due to
  - the high measurement effort nowadays without any additional value (as factor are similar/identical)
  - the procedure is not reproducible due to measurement inaccuracies caused by small REESS compared to absolute CO<sub>2</sub> values; therefore massively different corrections could be the consequence)
- It should be at the option of the manufacturer to use a generic worst case correction or to use a physically determined K<sub>CO2</sub> factor
- Proposal: Use of the pure ICE vehicle approach but apply different generator efficiency depending in the case of REESS charging
  - → Generator efficiency "n<sub>alternator</sub> = 1" is "Worst case approach"

	Willans Factor	Generator efficiency with neg. REESS Balance (Discharging)	Generator efficiency with pos. REESS Balance (Charging)
Diesel (B7)	161 (unchanged)	0,67	1
Petrol (E10)	184 (unchanged)	0,67	1

Calculation of CO<sub>2</sub>-Delta which need to be corrected:

$$\Delta M_{CO2,j} = 0{,}0036 \times \Delta E_{REESS,j} \times \frac{1}{\eta_{alternator}} \times Willans_{factor} \times \frac{1}{d_j}$$

→ With  $n_{alternator} = 1$  → smallest  $\Delta M_{CO2,j}$ 

Calculation of corrected CO<sub>2</sub> value:


$$M_{CO2,c,3} = M_{CO2,c,2} - \Delta M_{CO2,j}$$

 $\rightarrow$  With smallest  $\Delta M_{CO2,j} \rightarrow$  highest  $M_{CO2,c,3}$ 

### NOVC-HEV/NOVC-FCHV: CO<sub>2</sub>/FC correction

Proposal ACEA EV for SG EV (example here based on NOVC-HEV) (added: March 4th)

Explanation why assuming a generator efficiency of 100% ( $n_{alternator} = 1$ ) is the worst case in the context of  $CO_2/FC$  correction



Is the generic approach also the worst case compared to  $K_{CO2}$  derived by measurements?

→ Yes, because measurements reflect real life situation and therefore a generator efficiency of less than 100% (which is not the worst case)

## (N)OVC-HEV: K<sub>CO2</sub> correction factor family

Updated proposal ACEA EV for SG EV (status: February 26th)

K<sub>CO2</sub> family for NOVC-HEVs and OVC-HEVs

Only OVC-HEVs and NOVC-HEVs that are identical with respect to the following characteristics may be part of the same  $K_{CO2}$  family at which  $K_{CO2}$  shall be determined with vehicle H of one of the included interpolation families:

- Type of internal combustion engine: fuel type (or types in the case of flex-fuel or bi-fuel vehicles), combustion process, engine capacity, full-load characteristics, engine technology, and charging system, and also other engine subsystems or characteristics that have a non-negligible influence on CO2 mass emission K<sub>CO2</sub> under WLTP conditions;
- b. Operation strategy of all CO2 mass emission K<sub>CO2</sub> influencing components within the powertrain;
- c. Transmission type (e.g. manual, automatic, CVT) and transmission model (e.g. torque rating, number of gears, number of clutches, etc.);
- d. Type and number of electric machines: construction type (asynchronous/ synchronous, etc.), type of coolant (air, liquid) and any other characteristics having have a non-negligible influence on CO2 mass emission and electric energy consumption K<sub>CO2</sub> under WLTP conditions;
- e. Type of traction REESS (model, capacity, nominal voltage, nominal power, type of coolant (air, liquid));
- f. Type of electric energy converter between the electric machine and traction REESS and between the traction REESS and low voltage power supply and between the recharge-plug-in and traction REESS, and any other characteristics a non-negligible influence on CO2 mass emission and electric energy consumption K<sub>CO2</sub> under WLTP conditions. At the request of the manufacturer and with the approval of the approval authority, electric energy converters between recharge-plug-in and traction REESS with lower recharge losses may be included in the family;